



TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR MATERIAL: PBT
 FLAMMABILITY RATING UL94-V0
 COLOUR: WHITE
 CONTACT MATERIAL: COPPER ALLOY
 CONTACT TYPE: STAMPED
 CONTACT PLATING: SELECTIVE GOLD
 SHIELDING: BRASS NI PLATED
 QUALITY CLASS: 1500 MATING CYCLES

ENVIRONMENTAL
 OPERATING TEMPERATURE: -40 °C UP TO 105 °C
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
 CURRENT RATING: 1 A
 WORKING VOLTAGE: 30 V
 INSULATION RESISTANCE: >1000 MOHM
 DIELECTRIC WITHSTANDING VOLTAGE: 750 VAC/MN
 CONTACT RESISTANCE: 20 mOHM MAX

STANDARD
 CERTIFIED: E323964 / MODEL NUMBER 61400413321

SOLDERING
 WAVE PROCESS ONLY

PACKAGING
 TRAY

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		DESCRIPTION: USB TYPE B VERTICAL WERI PART NO: 614 004 133 21	SIZE
G								A4
F	29-JUL-10	PIN NUMBERING	JC					
E	29-JAN-10	TOL.14.8 +/- 0.35	JP					
D	19-NOV-09	STANDARD	JP					
C	30-OCT-08	DRAWING	CH	APPROVAL: RJ	UNIT: MM			
B	07-FEB-08	PIN POSITIONS	CH		SCALE:			
A	20-NOV-07	PDF	CH		SHEET: 1/1			
REV	DATE	FILE	BY		DRAW:			