D-Sub Connector Covers > **D-Subminiature**

How are slimline adapters used?



Allow two same gender connectors to mate. Very handy to have on hand to solve problems in the field or lab. See detail 1.

See The Video

www.L-com.com/Videos/A24

Can also be used as pass through connectors for panel mounting.

Note: See the tip on page 147 for panel mounting hardware required. See detail 3.

Socket Savers:


Tip

Extend the life of more expensive D-Sub connectors on PCBs and cable assemblies that are subject to frequent mating and unmating. See detail 2. Can also be used as pass through connectors for panel mounting.

Null Modem, Reverser and Custom Wired Adapters:

are constructed

Convert existing straight wired cables to the desired wiring scheme.



Can also be used for panel mounting.

How slimline adapters All slimline adapters are fully shielded providing applications requiring frequent connector EMI protection in electrically noisy environments. Gender Changers and Socket Savers use a one piece contact design ensuring reliability in

1

mating/unmating. Standard mating hardware is easily removed and replaced for situations such as mismatched hardware, panel mounting, etc.

Slim-Line adapters are used in a variety of applications, as illustrated here. Due to their low profile, they help reduce

F F Μ

leverage strain on overstressed interface ports. (F = Female Connector, M = Male Connector)

М F

	Adapters and Reversers	Gender Changer / Socket Saver	Mating Hardware Durability Mating / Unmating Temperature Rating Current Rating Voltage Rating		ng Apj -55 5 a	Brass, Nickel Plated Approx. 100 cycles -55°C to 105°C 5 amps max. 50 volts max.	
			Compo	nents	Mat	erials	
1	Π		Hollow Rivet Female Connector Shell Female Connector Housing		Steel /	Steel / Tin Plated Steel / Tin Plated	
-					Steel /		
					Glass filled PBT, UL94 V-0 rated		
e			Metal S	hield	Steel /	Tin Plated	
	РСВ		Conta	cts i	Brass / Gol	d Flash Plated	
		Male / Female Contacts	Male Connector Housing Male Connector Shell		Glass filled PBT, UL94 V-0 rated Steel / Tin Plated		
_							
Item #	Description		1-9	10-24	25-99	100-249	250-499
Rolls DBS	9 and DB25 Shielded Covers	- Protect Ports from Contamin	nation and El	MI			
	all metal covers provide port protection sitive attachment and proper groundi	on and shielding from EMI/RFI interferencing.	e. Unlike other co	overs, the DM	L series	is equipped	with 4-40
DML009P	Shielded Cover for DB9M		1.59	1.46	1.34	1.21	1.08
DML009S DML019P	Shielded Cover for DB9F Shielded Cover for DB25M		1.59 1.59	1.46 1.46	1.34 1.34	1.21 1.21	1.08 1.08
DML019S	Shielded Cover for DB25F		1.59	1.46	1.34	1.21	1.08
RoHS D-S	Sub Connector Covers - Prot	ect Unused Ports, Pkg/10					
		orts, cables or any expensive equipment or in place with a snug friction fit. Color is		damage, dir	t, and di	ust. Made fr	om RoHS
CVR9E	DB9/HD15 Protective Cover for		6.75	6.21	5.67	5.13	4.59
CVR9M	DB9/HD15 Protective Cover for		6.75	6.21	5.67	5.13	4.59

6.75

6.75

6.75

6.75

6.21

6.21

6.21

6.21

5.67

5.67

5.67

5.67

5.13

5.13

5.13

5.13

4.59

4.59

4.59

4 59



How slim-line adapters are constructed See the tip and more at L-com.com/SlimlineConstruction

DB15/HD26 Protective Cover for Female Connectors, Pkg/10

DB25/HD44 Protective Cover for Female Connectors, Pkg/10

DB15/HD26 Protective Cover for Male Connectors, Pkg/10

DB25/HD44 Protective Cover for Male Connectors, Pkg/10

Shop at L-com.com or call 1-800-343-1455

E-mail: sales@L-com.com Fax: 978-689-9484

CVR15F

CVR15M

CVR25F

CVR25M