



JB85 Cross Spacing Jumpers

Terminal Blocks Accessories



Features and Benefits

Allows power distribution between 8 mm *0.315 in* and 5.2 mm *0.205 in* spacing feed-through terminal blocks.

Main Technical Data

	IEC	cULus - CSA	Ex e
Rated current	32 A	30 A	
Rated voltage	Standard use 1000 V	600 V	630 V
	Cut extremities 800 V	300 V	Not authorized
	Cut poles 630 V	300 V	Not authorized
Impulse withstand voltage	8000 V		
Protection	IP 20	NEMA 1	

Mounting Instructions

Screwless


Tool

Torque


Material Specifications	Insulating material	Polyamide	
	Flammability	V0	
	NF F 16 101	I2F2	
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C	-67 +230 F
	Storage	-55 +110 °C	-67 +230 F
	Installing	-5 +40 °C	-23 +104 F

Ordering Details

JB85 Cross Spacing Jumpers

Description	Type	Order Code	Pack ^(n°) pieces	Weight g (1 pce)
8 mm <i>0.315 in</i> to 5.2 mm <i>0.205 in</i> spacing 3 poles	Orange  JB85-3	1SNK 900 603 R0000	10	2.80

JB85 Mounting Instructions



Be careful with the current limitation:
 $I1 + I2 \leq I_{max}$