

Connectors for consumer electronics

MAS/MAK-series

HiMedia

Product description













Shielded miniature multipole connectors, 3- pole to 8-pole.

- Numerous different versions ensure a variety of uses in audio- and video equipment, measurement and control instruments, on projectors and in the computer technology

- Safe connection of connector, couplings, panel-mounted sockets and panel-mounted connectors with screw locking system
- All cable connectors feature clamping tabs to relieve the strain
- UM types as standard, but industry package, quantity boxed: 1000 units

Basic data

Operating voltage: 34 V AC / DC
 Operating current: 4 A
 Flashover voltage: 1 kV
 Insulation resistance: $10^{11} \Omega$
 Type of connection: solder
 Plug illustrations: EN 60130-9

Type		Number of poles	Description	Colour	Order no.
 MAS 30 MAS 30 UM		3 	Connector with insulated handle, solder connection	grey UM black UM grey	930 014-517 931 002-100 931 002-117
 MAS 40 MAS 40 UM		4 	Connector with insulated handle, solder connection	grey UM grey	930 015-517 931 018-117
 MAS 50 MAS 50 UM		5 	Connector with insulated handle, solder connection	grey UM black UM grey	930 016-517 931 034-100 931 034-117
 MAS 50 S MAS 50 S UM		5 	Connector with insulated handle, solder connection	black grey UM black UM grey	930 131-500 930 131-517 931 036-100 931 036-117