

PART NO.


2318 Series


REVISIONS								
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	24/3/08	Suresh	24/3/08	Farnell	07/4/08


RoHS


Compliant

Crimp Housing










Specifications:


Current rating : 3.0 A ac/dc. : 250V ac/dc. Voltage rating Maximum contact resistance : 20mΩ. Minimum insulation resistance : $1000M\Omega$.


Withstanding voltage : 1000V ac/minute. Operating temperature range : -40°C to +85°C. Application wire : #22 to 28AWG. Materials:

Insulator : High temperature plastic (Nylon 66). Insulator colour : Black.

Contact : Phosphor bronze. : Tin Plated. Plated







Dimensions : Millimetres

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

TOLERANCES:

DRAWN BY:	DATE:
Veena	24/03/08
CHECKED BY:	DATE:
Suresh	24/03/08
APPROVED BY:	DATE:
Farnell	07/04/08

E:	DRAWING TITLE:								
8	2.5mm Crimp Housing - Wire-to-Board								
Ε:	SIZE	DWG NO.	M10001975		ELECTRONIC FILE 1697893-TDS_DWG				REV
8	Α							/G	Α
E: 8	SCALE: NTS		U.O.M.: mm	U.O.M.: mm		1	OF	3	





PART NO.


2318 Series


		REVISIONS						
ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Veena	24/3/08	Suresh	24/3/08	Farnell	07/4/08

Accessories - Crimp Pin









Section : A-A

Specifications:

Current rating : 3.0A ac/dc. Voltage rating : 250V ac/dc. Minimum contact resistance : 20m Ω .

Withstanding voltage : $1000M\Omega$ for one minute. Withstanding voltage : 800V ac/minute. Temperature range : -25°C to +125°C. : #28 to 24AWG. Application wires

Material and Finish:

Contact : Phosphor bronze. Finish : Tin plated.

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
Veena	24/03/08
CHECKED BY:	DATE:
Suresh	24/03/08
APPROVED BY:	DATE:
Farnell	07/04/08

E:	DRAW	NG TITLE:							
8	2.5mm Crimp Housing - Wire-to-Board								
E:	SIZE	DWG NO.			ELEC	TRONIC FIL	LE.	П	REV
8	Α			M10001975		893-TDS_		G	Α
E: 18	SCALE: NTS		U.O.M.: mm		SHEET:	2	OF	3	



PART NO.

2318 Series

	REVISIONS								
E	ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
	-	Α	RELEASED	Veena	24/3/08	Suresh	24/3/08	Farnell	07/4/08

Specification Table

Туре	Number of Position	Α	В	Part Number
	2	2.50	6.00	2318HB-02
	3	5.00	8.50	2318HB-03
	4	7.50	11.00	2318HB-04
Crimp Housing	5	10.00	13.50	2318HB-05
Chilip Housing	6	12.50	16.00	2318HB-06
	8	17.50	21.00	2318HB-08
	10	22.50	26.00	2318HB-10
	12	27.50	31.00	2318HB-12
Crimp Pin	-	-	-	2318TB

Dimensions : Millimetres

Part Number Explanation: **Crimp Housing**

2318



Number of Positions: 02 = 2, 03 = 3, 04 = 4, 05 = 5, 06 = 6, 08 = 8, 10 and 12 Positions.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

REV

Α

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:	DRAWING TITLE		
Veena	24/03/08			
CHECKED BY:	DATE:	SIZE	DWG NO	
Suresh	24/03/08	Α		
APPROVED BY:	DATE:	- ` `		
Farnell	07/04/08	SCAL	E: NTS	

2.5mm Crimp Housing - Wire-to-Board ELECTRONIC FILE DWG NO. SIZE M10001975 1697893-TDS_DWG Α SCALE: NTS U.O.M.: mm SHEET: 3 OF 3