

## Features

### Printed circuit mount 16 A Power relay

- 2 & 3 Pole changeover contacts or NO ( $\geq 3$  mm contact gap)
- AC coils & DC coils
- Reinforced insulation between coil and contacts according to EN 60335-1, with 6 mm clearance & 8 mm creepage distance
- SELV coil-contact separator option
- Cadmium Free contact material options

### 62.22 / 62.23




- 2 & 3 pole changeover contact
- PCB mount

### 62.22-0300 / 62.23-0300




- 2 & 3 pole normally open contact ( $\geq 3$  mm contact gap)
- PCB mount



\* Distance between contacts  $\geq 3$  mm (EN 60730-1).


\*\* With the  $\text{AgSnO}_2$  material the maximum peak current is 120 A - 5 ms (NO contact).

FOR UL HORSEPOWER AND PILOT DUTY RATINGS  
SEE "General technical information" page V



62.22  
Copper side view

62.23  
Copper side view



62.22-0300  
Copper side view

62.23-0300  
Copper side view

### Contact specification

Contact configuration	2 CO (DPDT)	3 CO (3PDT)	2 NO (DPST-NO), $\geq 3$ mm*	3 NO (3PST-NO), $\geq 3$ mm*
Rated current/Maximum peak current	A 16/30**		16/30**	
Rated voltage/Maximum switching voltage V AC	250/400		250/400	
Rated load AC1	VA 4,000		4,000	
Rated load AC15 (230 V AC)	VA 750		750	
Motor rating (230/400 V AC)	kW 0.8/—		0.8/—	
Breaking capacity DC1: 30/110/220 V	A 16/0.6/0.4		16/1.1/0.7	
Minimum switching load	mW (V/mA) 1,000 (10/10)		1,000 (10/10)	
Standard contact material	AgCdO		AgCdO	

### Coil specification

Nominal voltage ( $U_N$ )	V AC (50/60 Hz)	6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400	
	V DC	6 - 12 - 24 - 48 - 60 - 110 - 125 - 220	
Rated power AC/DC	VA (50 Hz)/W	2.2/1.3	3/3
Operating range	AC	$(0.8 \dots 1.1) U_N$	
	DC	$(0.8 \dots 1.1) U_N$	
Holding voltage	AC/DC	$0.8 U_N / 0.6 U_N$	
Must drop-out voltage	AC/DC	$0.2 U_N / 0.1 U_N$	

### Technical data

Mechanical life AC/DC	cycles	$10 \cdot 10^6 / 30 \cdot 10^6$	$10 \cdot 10^6 / 30 \cdot 10^6$
Electrical life at rated load AC1	cycles	$100 \cdot 10^3$	$100 \cdot 10^3$
Operate/release time	ms	10/10	20/4
Insulation between coil and contacts (1.2/50 $\mu$ s)	kV	6	6
Dielectric strength between open contacts	V AC	1,500	2,500
Ambient temperature range	$^{\circ}\text{C}$	-40...+70	-40...+50
Environmental protection		RT I	RT I

### Approvals (according to type)



## Features


### Plug-in mount/Faston 187 16 A Power relay

- Plug-in (92 series sockets) or Faston 187 (4.8x0.5 mm) with optional mounting adaptors
- 2 & 3 Pole changeover contacts or NO ( $\geq 3$  mm contact gap)
- AC coils & DC coils
- UL Listing (certain relay/socket combinations)
- LED, mechanical indicator & test button options
- Reinforced insulation between coil and contacts according to EN 60335-1, with 6 mm clearance & 8 mm creepage distance
- SELV coil-contact separator option
- Cadmium Free contact material options
- Sockets and accessories

### 62.32 / 62.33




- 2 & 3 pole changeover contact
- Plug-in / Faston 187



### 62.32-0300 / 62.33-0300





- 2 & 3 pole normally open contact ( $\geq 3$  mm contact gap)
- Plug-in / Faston 187



- \* Distance between contacts  $\geq 3$  mm (EN 60730-1).
- \*\* With the AgSnO<sub>2</sub> material the maximum peak current is 120 A - 5 ms (NO contact).

FOR UL HORSEPOWER AND PILOT DUTY RATINGS  
SEE "General technical information" page V



Contact specification		2 CO (DPDT)		3 CO (3PDT)		2 NO (DPSTNO), $\geq 3$ mm*		3 NO (3PSTNO), $\geq 3$ mm*	
Contact configuration		2 CO (DPDT)		3 CO (3PDT)		2 NO (DPSTNO), $\geq 3$ mm*		3 NO (3PSTNO), $\geq 3$ mm*	
Rated current/Maximum peak current	A	16/30**		16/30**		16/30**		16/30**	
Rated voltage/Maximum switching voltage V AC		250/400		250/400		250/400		250/400	
Rated load AC1	VA	4,000		4,000		4,000		4,000	
Rated load AC15 (230 V AC)	VA	750		750		750		750	
Motor rating (230/400 V AC)	kW	0.8/—		0.8/1.5		0.8/—		0.8/1.5	
Breaking capacity DC1: 30/110/220 V	A	16/0.6/0.4		16/1.1/0.7		16/1.1/0.7		16/1.1/0.7	
Minimum switching load	mW (V/mA)	1,000 (10/10)		1,000 (10/10)		1,000 (10/10)		1,000 (10/10)	
Standard contact material		AgCdO		AgCdO		AgCdO		AgCdO	
Coil specification									
Nominal voltage (U <sub>N</sub> )	V AC (50/60 Hz)	6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400							
	V DC	6 - 12 - 24 - 48 - 60 - 110 - 125 - 220							
Rated power AC/DC	VA (50 Hz)/W	2.2/1.3				3/3			
Operating range	AC	(0.8...1.1)U <sub>N</sub>				(0.85...1.1)U <sub>N</sub>			
	DC	(0.8...1.1)U <sub>N</sub>				(0.85...1.1)U <sub>N</sub>			
Holding voltage	AC/DC	0.8 U <sub>N</sub> /0.6 U <sub>N</sub>				0.8 U <sub>N</sub> /0.6 U <sub>N</sub>			
Must drop-out voltage	AC/DC	0.2 U <sub>N</sub> /0.1 U <sub>N</sub>				0.2 U <sub>N</sub> /0.1 U <sub>N</sub>			
Technical data									
Mechanical life AC/DC	cycles	10 · 10 <sup>6</sup> /30 · 10 <sup>6</sup>				10 · 10 <sup>6</sup> /30 · 10 <sup>6</sup>			
Electrical life at rated load AC1	cycles	100 · 10 <sup>3</sup>				100 · 10 <sup>3</sup>			
Operate/release time	ms	10/10				20/4			
Insulation between coil and contacts (1.2/50 μs)	kV	6				6			
Dielectric strength between open contacts	V AC	1,500				2,500			
Ambient temperature range	°C	-40...+70				-40...+50			
Environmental protection		RT I				RT I			
Approvals (according to type)									

## Features

### Flange mount/Faston 250 16 A Power relay

- Faston 250 (6.3x0.8 mm) termination Flange or optional mounting adaptors
- 2 & 3 Pole changeover contacts or NO ( $\geq 3$  mm contact gap)
- AC coils & DC coils
- LED, mechanical indicator & test button options
- Reinforced insulation between coil and contacts according to EN 60335-1, with 6 mm clearance & 8 mm creepage distance
- SELV coil-contact separator option
- Cadmium Free contact material options

\* Distance between contacts  $\geq 3$  mm (EN 60730-1).



\*\* With the  $\text{AgSnO}_2$  material the maximum peak current is 120 A - 5 ms (NO contact).

FOR UL HORSEPOWER AND PILOT DUTY RATINGS  
SEE "General technical information" page V

### 62.82 / 62.83





- 2 & 3 pole changeover contact
- Flange mount / Faston 250



### 62.82-0300 / 62.83-0300



- 2 & 3 pole normally open contact ( $\geq 3$  mm contact gap)
- Flange mount / Faston 250



Contact specification		62.82		62.83		62.82-0300		62.83-0300	
Contact configuration		2 CO (DPDT)		3 CO (3PDT)		2 NO (DPSTNO), $\geq 3$ mm*		3 NO (3PSTNO), $\geq 3$ mm*	
Rated current/Maximum peak current	A	16/30**		16/30**		16/30**		16/30**	
Rated voltage/Maximum switching voltage	V AC	250/400		250/400		250/400		250/400	
Rated load AC1	VA	4,000		4,000		4,000		4,000	
Rated load AC15 (230 V AC)	VA	750		750		750		750	
Motor rating (230/400 V AC)	kW	0.8/—		0.8/1.5		0.8/—		0.8/1.5	
Breaking capacity DC1: 30/110/220 V	A	16/0.6/0.4		16/0.6/0.4		16/1.1/0.7		16/1.1/0.7	
Minimum switching load	mW (V/mA)	1,000 (10/10)		1,000 (10/10)		1,000 (10/10)		1,000 (10/10)	
Standard contact material		AgCdO		AgCdO		AgCdO		AgCdO	
Coil specification		62.82		62.83		62.82-0300		62.83-0300	
Nominal voltage ( $U_N$ )	V AC (50/60 Hz)	6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400		6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400		6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400		6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400	
	V DC	6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400		6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400		6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400		6 - 12 - 24 - 48 - 60 - 110 - 120 - 230 - 240 - 400	
Rated power AC/DC	VA (50 Hz)/W	2.2/1.3		2.2/1.3		3/3		3/3	
Operating range	AC	$(0.8 \dots 1.1) U_N$		$(0.8 \dots 1.1) U_N$		$(0.85 \dots 1.1) U_N$		$(0.85 \dots 1.1) U_N$	
	DC	$(0.8 \dots 1.1) U_N$		$(0.8 \dots 1.1) U_N$		$(0.85 \dots 1.1) U_N$		$(0.85 \dots 1.1) U_N$	
Holding voltage	AC/DC	0.8 $U_N$ /0.6 $U_N$		0.8 $U_N$ /0.6 $U_N$		0.8 $U_N$ /0.6 $U_N$		0.8 $U_N$ /0.6 $U_N$	
Must drop-out voltage	AC/DC	0.2 $U_N$ /0.1 $U_N$		0.2 $U_N$ /0.1 $U_N$		0.2 $U_N$ /0.1 $U_N$		0.2 $U_N$ /0.1 $U_N$	
Technical data		62.82		62.83		62.82-0300		62.83-0300	
Mechanical life AC/DC	cycles	10 · 10 <sup>6</sup> /30 · 10 <sup>6</sup>		10 · 10 <sup>6</sup> /30 · 10 <sup>6</sup>		10 · 10 <sup>6</sup> /30 · 10 <sup>6</sup>		10 · 10 <sup>6</sup> /30 · 10 <sup>6</sup>	
Electrical life at rated load AC1	cycles	100 · 10 <sup>3</sup>		100 · 10 <sup>3</sup>		100 · 10 <sup>3</sup>		100 · 10 <sup>3</sup>	
Operate/release time	ms	10/10		10/10		20/4		20/4	
Insulation between coil and contacts (1.2/50 $\mu$ s)	kV	6		6		6		6	
Dielectric strength between open contacts	V AC	1,500		1,500		2,500		2,500	
Ambient temperature range	°C	-40...+70		-40...+70		-40...+50		-40...+50	
Environmental protection		RT I		RT I		RT I		RT I	
Approvals (according to type)		CE		SR		PG		Y	
		RINA		S		CULUS		VDE	

## Ordering information

Example: 62 series power relay + Faston 250 (6.3x0.8 mm), rear flange mount, 2 NO (DPST-NO), 12 V DC coil.

	<b>6</b>	<b>2</b>	<b>8</b>	<b>2</b>	<b>9</b>	<b>0</b>	<b>1</b>	<b>2</b>	<b>0</b>	<b>3</b>	<b>0</b>	<b>0</b>
<b>Series</b>												
<b>Type</b>												
2 = PCB												
3 = Plug-in												
8 = Faston 250 (6.3x0.8 mm) with rear flange mount												
<b>No. of poles</b>												
2 = 2 pole												
3 = 3 pole												
<b>Coil version</b>												
8 = AC (50/60 Hz)												
9 = DC												
<b>Coil voltage</b>												
See coil specifications												
	<b>A: Contact material</b>			<b>B: Contact circuit</b>			<b>C: Options</b>			<b>D: Special versions</b>		
	0 = Standard AgCdO 4 = AgSnO <sub>2</sub>			0 = CO (nPDT) 3 = NO (nPST), ≥ 3 mm contact gap 5 = CO (nPDT) + additional physical separator between coil and contacts (for SELV applications) 6 = NO (nPST), ≥ 3 mm contact gap + additional physical separator between coil and contacts (for SELV applications)			0 = None 2 = Mechanical indicator 3 = LED (AC) 4 = Lockable test button + mechanical indicator 5* = Lockable test button + LED (AC) 54* = Lockable test button + LED (AC) + mechanical indicator 6* = LED + diode (DC, polarity positive to pin A/A1) 7* = Lockable test button + LED + diode (DC, polarity positive to pin A/A1) 74* = Lockable test button + LED + diode (DC, polarity positive to pin A/A1) + mechanical indicator			0 = Standard 5 = Top flange mount 6 = Rear flange mount 7 = Top 35 mm rail (EN 50022) mount 8 = Rear 35 mm rail (EN 50022) mount 9 = Type 62.82/83 without rear flange mount		

**Selecting features and options: only combinations in the same row are possible.**  
Preferred selections for best availability are shown in **bold**.

Type	Coil version	A	B	C	D
62.22/23	AC-DC	<b>0</b> - 4	<b>0</b> - 3 - 5 - 6	<b>0</b>	<b>0</b>
62.32/33	AC-DC	0 - 4	0 - 3 - 5 - 6	0	0 - 5 - 6 - 7 - 8
	AC-DC	<b>0</b> - 4	<b>0</b> - 5	2 - <b>4</b>	<b>0</b> - 6 - 8
	AC	<b>0</b> - 4	<b>0</b>	2 - 3 - <b>4</b> - 5	<b>0</b> - 6 - 8
	AC	0 - 4	0 - 3	3	0 - 6 - 8
	AC	0 - 4	0	54	/
	DC	<b>0</b> - 4	<b>0</b>	<b>4</b> - 6 - 7	<b>0</b> - 6 - 8
	DC	0 - 4	0 - 3	6	0 - 6 - 8
62.82/83	AC-DC	<b>0</b> - 4	<b>0</b> - 3 - 5 - 6	<b>0</b>	<b>0</b> - 5 - 7 - 8 - 9
	AC-DC	0 - 4	0 - 5	2 - 4	0 - 8
	AC	0 - 4	0	2 - 3 - 4 - 5	0 - 8
	AC	0 - 4	0 - 3	3	0 - 8
	DC	0 - 4	0	4 - 6 - 7	0 - 8
	DC	0 - 4	0 - 3	6	0 - 8

\* Options not available for 220 V DC and 400 V AC versions.

## Descriptions: Options and Special versions

<b>C: Option 3, 5, 54</b> LED (AC)	<b>C: Option 6, 7, 74</b> LED + diode (DC, polarity positive to pin A/A1)	<b>D: Special versions 5</b> Top flange mount	<b>D: Special versions 7</b> Top 35 mm rail (EN 50022) mount	<b>B: Contact circuit 5, 6</b> Additional physical separator between coil and contacts (for SELV applications)



### Lockable test button and mechanical flag indicator (0040, 0050, 0054, 0070, 0074)

The dual-purpose Finder test button can be used in two ways:

**Case 1)** The plastic pip (located directly above the test button) remains intact. In this case, when the test button is pushed, the contacts operate. When the test button is released the contacts return to their former state.

**Case 2)** The plastic pip is broken-off (using an appropriate cutting tool). In this case, (in addition to the above function), when the test button is pushed and rotated, the contacts are latched in the operating state, and remain so until the test button is rotated back to its former position.


In both cases ensure that the test button actuation is swift and decisive.

**Technical data**

<b>Insulation according to EN 61810-1:2004</b>		<b>2 CO - 3 CO</b>		<b>2 NO - 3 NO</b>	
Nominal voltage of supply system	V AC	230/400		230/400	
Rated insulation voltage	V AC	400		400	
Pollution degree		3		3	
<b>Insulation between coil and contact set</b>					
Type of insulation		Reinforced		Reinforced	
Overvoltage category		III		III	
Rated impulse voltage	kV (1.2/50 µs)	6		6	
Dielectric strength	V AC	4,000		4,000	
<b>Insulation between adjacent contacts</b>					
Type of insulation		Basic		Basic	
Overvoltage category		III		III	
Rated impulse voltage	kV (1.2/50 µs)	4		4	
Dielectric strength	V AC	2,500		2,500	
<b>Insulation between open contacts</b>					
Type of disconnection		Micro-disconnection		Full-disconnection	
Overvoltage category		—		III	
Rated impulse voltage	kV (1.2/50 µs)	—		4	
Dielectric strength	V AC/kV (1.2/50 µs)	1,500/2		2,500/4	
<b>Conducted disturbance immunity</b>					
Burst (5...50)ns, 5 kHz, on A1 - A2		EN 61000-4-4		level 4 (4 kV)	
Surge (1.2/50 µs) on A1 - A2 (differential mode)		EN 61000-4-5		level 4 (4 kV)	
<b>Other data</b>					
Bounce time: NO/NC	ms	3/6 (changeover)		3/— (normally open)	
Vibration resistance (10...150)Hz: NO/NC	g	20/8			
Shock resistance	g	15			
Power lost to the environment		<b>2 pole (CO)</b>	<b>3 pole (CO)</b>	<b>2 pole (NO)</b>	<b>3 pole (NO)</b>
	without contact current	W	1.3	1.3	3
	with rated current	W	3.3	4.3	5
Recommended distance between relays mounted on PCB	mm	≥ 5			


## Contact specification

F 62 - Electrical life (AC) v contact current




H 62 - Maximum DC1 breaking capacity

Changeover contacts



H 62 - Maximum DC1 breaking capacity

Normally open contacts



- When switching a resistive load (DC1) having voltage and current values under the curve, an electrical life of  $\geq 100 \cdot 10^3$  can be expected.
- In the case of DC13 loads, the connection of a diode in parallel with the load will permit a similar electrical life as for a DC1 load.

Note: the release time of the load will be increased.

## Coil specifications

### DC version data

Nominal voltage $U_N$	Coil code	Operating range		Resistance R	Rated coil consumption I at $U_N$
		$U_{min}$	$U_{max}$		
V		V	V	$\Omega$	mA
6	9.006	4.8	6.6	28	214
12	9.012	9.6	13.2	110	109
24	9.024	19.2	26.4	445	54
48	9.048	38.4	52.8	1,770	27
60	9.060	48	66	2,760	21.7
110	9.110	88	121	9,420	11.7
125	9.125	100	137.5	12,000	10.4
220	9.220	176	242	37,300	5.8

### AC version data

Nominal voltage $U_N$	Coil code	Operating range		Resistance R	Rated coil consumption I at $U_N$ (50Hz)
		$U_{min}$	$U_{max}$		
V		V	V	$\Omega$	mA
6	8.006	4.8	6.6	4.6	367
12	8.012	9.6	13.2	19	183
24	8.024	19.2	26.4	74	90
48	8.048	38.4	52.8	290	47
60	8.060	48	66	450	37
110	8.110	88	121	1,600	20
120	8.120	96	132	1,940	18.6
230	8.230	184	253	7,250	10.5
240	8.240	192	264	8,500	9.2
400	8.400	320	440	19,800	6

### DC (NO/nPST-NO) version data - $\geq 3$ mm


Nominal voltage $U_N$	Coil code	Operating range		Resistance R	Rated coil consumption I at $U_N$
		$U_{min}$	$U_{max}$		
V		V	V	$\Omega$	mA
6	9.006	5.1	6.6	12	500
12	9.012	10.2	13.2	48	250
24	9.024	20.4	26.4	192	125
48	9.048	40.8	52.8	770	63
60	9.060	51	66	1,200	50
110	9.110	93.5	121	4,200	26
125	9.125	106.2	137.5	5,200	24
220	9.220	187	242	17,600	12.5

### AC (NO/nPST-NO) version data - $\geq 3$ mm

Nominal voltage $U_N$	Coil code	Operating range		Resistance R	Rated coil consumption I at $U_N$ (50Hz)
		$U_{min}$	$U_{max}$		
V		V	V	$\Omega$	mA
6	8.006	5.1	6.6	4	540
12	8.012	10.2	13.2	14	275
24	8.024	20.4	26.4	62	130
48	8.048	40.8	52.8	220	70
60	8.060	51	66	348	55
110	8.110	93.5	121	1,200	30
120	8.120	106	137	1,350	24
230	8.230	196	253	5,000	14
240	8.240	204	264	6,300	12.5
400	8.400	340	440	14,700	7.8


### R 62 - DC coil operating range v ambient temperature

Changeover contacts




### R 62 - AC coil operating range v ambient temperature

Changeover contacts




### R 62 - DC coil operating range v ambient temperature

Normally open contacts



### R 62 - AC coil operating range v ambient temperature

Normally open contacts



- 1 - Max. permitted coil voltage.  
2 - Min. pick-up voltage with coil at ambient temperature.





- 1 - Max. permitted coil voltage.  
2 - Min. pick-up voltage with coil at ambient temperature.

## Accessories



**Mounting adaptor** for types 62.3x and 62.8x.xxxx.xxx9 (M4)

062.10






062.10

062.10 with relay



**Flange mounting adaptor** for types 62.3x and 62.8x.xxxx.xxx9

062.60



062.60

062.60 with relay



**Sheet of marker tags** for 62 series relays, plastic, 72 tags, 6x12 mm

060.72






Approvals  
(according to type):



<b>Screw terminal (Box clamp) socket</b>	<b>92.03</b>	<b>92.03.0</b>
panel or 35 mm rail (EN 50022) mount	<b>Blue</b>	<b>Black</b>
For relay type	62.32, 62.33	
<b>Accessories</b>		
Metal retaining clip (supplied with socket - packaging code SMA)		092.71
Identification tag		092.00.2
Modules (see table below)		99.02
Timer modules (see table below)		86.00, 86.30
<b>Technical data</b>		
Rated values	16 A - 250 V	
Insulation	6 kV (1.2/50 μs) between coil and contacts	
Protection category	IP 20	
Ambient temperature	°C	-40...+70
⊕ Screw torque	Nm	0.8
Wire strip length	mm	10
Max. wire size for 92.03 socket		solid wire
	mm <sup>2</sup>	1x10 / 2x4
	AWG	1x8 / 2x12
		stranded wire
		1x6 / 2x4
		1x10 / 2x12



<b>86 series timer modules</b>		
Multi-voltage: (12...240)V AC/DC;		
Multi-functions: AI, DI, SW, BE, CE, DE, EE, FE; (0.05s...100h)		86.00.0.240.0000
(12...24)V AC/DC; Bi-function: AI, DI; (0.05s...100h)		86.30.0.024.0000
(230...240)V AC; Bi-function: AI, DI; (0.05s...100h)		86.30.8.240.0000

Approvals  
(according to type):



Approvals  
(according to type):



DC Modules with  
non-standard polarity  
(+A2) on request.


<b>99.02 coil indication and EMC suppression modules for 92.03 socket</b>		
Diode (+A1, standard polarity)	(6...220)V DC	99.02.3.000.00
LED	(6...24)V DC/AC	99.02.0.024.59
LED	(28...60)V DC/AC	99.02.0.060.59
LED	(110...240)V DC/AC	99.02.0.230.59
LED + Diode (+A1, standard polarity)	(6...24)V DC	99.02.9.024.99
LED + Diode (+A1, standard polarity)	(28...60)V DC	99.02.9.060.99
LED + Diode (+A1, standard polarity)	(110...220)V DC	99.02.9.220.99
LED + Varistor	(6...24)V DC/AC	99.02.0.024.98
LED + Varistor	(28...60)V DC/AC	99.02.0.060.98
LED + Varistor	(110...240)V DC/AC	99.02.0.230.98
RC circuit	(6...24)V DC/AC	99.02.0.024.09
RC circuit	(28...60)V DC/AC	99.02.0.060.09
RC circuit	(110...240)V DC/AC	99.02.0.230.09
Residual current by-pass	(110...240)V AC	99.02.8.230.07



Approvals  
(according to type):




PCB socket	92.13 (blue)	92.13.0 (black)
For relay type	62.32, 62.33	
<b>Accessories</b>		
Metal retaining clip (supplied with socket - packaging code SMA)	092.54	
<b>Technical data</b>		
Rated values	16 A - 250 V (10 A max for each contact circuit)	
Dielectric strength	2.5 kV AC	
Ambient temperature	°C -40...+70	



Approvals  
(according to type):



Panel mount solder socket mounted with M3 screw	92.33 (blue)
For relay type	62.32, 62.33
<b>Accessories</b>	
Metal retaining clip (supplied with socket - packaging code SMA)	092.54
<b>Technical data</b>	
Rated values	16 A - 250 V (10 A max for each contact circuit)
Dielectric strength	2.5 kV AC
Ambient temperature	°C -40...+70



## Packaging code

How to code and identify retaining clip and packaging options for sockets.

Example:

