




GUARDIAN Electric Manufacturing

ISO 9001 / AS9100 Certified Company

Woodstock, IL 60098 Ph. (815)334-3600 Fax (815)337-0377

Or visit us at our website www.guardian-electric.com

Model LT6 x 12 Long-Life DC Tubular Solenoid



Solenoid shown energized and fully seated.

Supplied with mounting bracket, hex nut and lockwasher (not shown).

Spring kits are available (consult factory).

Total Weight: 2.53 oz.

Plunger Weight: .57 oz.


Model No.	Part No.	Duty Cycle	Voltage	Resistance (Ω)	Power (W)	Current (mA)
LT6x12-I-12	A420-064835-00	Intermittent	12VDC	13.8	11	870
LT6x12-C-12	A420-064834-00	Continuous	12VDC	35	4.3	343
LT6x12-I-24	A420-064837-00	Intermittent	24VDC	53.8	11.2	446
LT6x12-C-24	A420-064836-00	Continuous	24VDC	138	4.4	174

When ordering, please refer to Part No., as listed above.

Consult factory for custom configurations.

Stroke (in.)	Pull Force (oz.)								Holding Force (oz.)
	0.050	0.125	0.250	0.375	0.500	0.625	0.750	1.000	
Continuous Duty	30	10	5	1	0.5	N/A	N/A	N/A	21
Intermittent Duty	45	22	10	5	1	N/A	N/A	N/A	39

UL Recognition

Recognized under the  Component Recognition Program of **Underwriters Laboratories, Inc.**

Continuous Duty

100% 'On' Time

Intermittent Duty

25% 'On' Time, (100 Seconds 'On' Max. Followed By 300 Seconds 'Off' Min.)

RoHS

These parts comply with **RoHS** Directive 2002/95/EC