



# PG5 Disconnect Plugs

## Terminal Blocks Accessories

### Features and Benefits

Allow disconnect function when associated with the ZS4-SP and ZS4-SP-R1 terminal blocks.

### Main Technical Data

|                           | IEC                | cULus - CSA | Ex e |
|---------------------------|--------------------|-------------|------|
| Rated current             | 18 A               | 20 A        |      |
| Rated voltage             | Standard use 400 V | 150 V       |      |
| Impulse withstand voltage | 6000 V             |             |      |
| Protection                | IP 20              | NEMA 1      |      |

### Mounting Instructions

Plug In

|        |
|--------|
| Tool   |
| Torque |

| Material Specifications     | Insulating material   | Polyamide   |            |
|-----------------------------|-----------------------|-------------|------------|
|                             | Flammability          | V0          |            |
|                             | NF F 16 101           | I2F2        |            |
| Ambient temperature min/max | Service IEC 60068-2-1 | -55 +110 °C | -67 +230 F |
|                             | Storage               | -55 +110 °C | -67 +230 F |
|                             | Installing            | -5 +40 °C   | -23 +104 F |

### Ordering Details

#### PG5 Disconnect Plugs

| Description               | Type                 | Order Code                | Pack <sup>(mg)</sup> pieces | Weight g (1 pce) |
|---------------------------|----------------------|---------------------------|-----------------------------|------------------|
| Equipped with linking bar | Orange <b>PG5-R1</b> | <b>1SNK 900 402 R0000</b> | 20                          | 3.45             |

#### PG5 Accessories

| Description                   | Type  | Order Code                | Pack <sup>(mg)</sup> pieces | Weight g (1 pce) |
|-------------------------------|---|---------------------------|-----------------------------|------------------|
| 1 Blank card                  | White <input type="checkbox"/> <b>MC512</b> | <b>1SNK 140 000 R0000</b> | 22                          | 0.06             |
| Universal wire markers holder | Grey <input type="checkbox"/> <b>UMH</b>    | <b>1SNK 900 611 R0000</b> | 10                          | 0.20             |
| Self adhesive strip           | White <input type="checkbox"/> <b>SAT5</b>  | <b>1SNK 900 614 R0000</b> | 5                           | 6.00             |

### PG5 Mounting Instructions

