




## PG5 Component Plugs

### Terminal Blocks Accessories



#### Features and Benefits

- Component holder compatible with 5.2 mm 0.205 in spacing SNK feed-through terminal blocks,
- Fit components 16 x 16 x 8.5 mm 0.630 x 0.630 x 0.335 in (not supplied with plug) such as resistors, diodes, varistance,
- Direct plug-in into the terminal blocks jumper channels,
- Maximum dissipated power: 2 W.

#### Main Technical Data

	IEC	cULus - CSA	Ex e
Rated current			
Rated voltage	Standard use 250 V		
Impulse withstand voltage	4000 V		
Protection	IP 20	NEMA 1	

#### Mounting Instructions

Plug In

Tool
Torque

Material Specifications	Insulating material	Polyamide	
Flammability	NF F 16 101	V0 I2F2	
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C	-67 +230 F
	Storage	-55 +110 °C	-67 +230 F
	Installing	-5 +40 °C	-23 +104 F

#### Ordering Details

##### PG5 Component Plugs

Description	Type	Order Code	Pack <sup>(mg)</sup> pieces	Weight g (1 pce)
Components insertion between 2 blocks	Dark Grey	<b>PG5-R2</b>	<b>1SNK 900 403 R0000</b>	20 8.01

##### PG5 Accessories

Description	Type	Order Code	Pack <sup>(mg)</sup> pieces	Weight g (1 pce)
1 Blank card	White <input type="checkbox"/>	<b>MC512</b>	<b>1SNK 140 000 R0000</b>	22 0.06
Universal wire markers holder	Grey <input type="checkbox"/>	<b>UMH</b>	<b>1SNK 900 611 R0000</b>	10 0.20
Self adhesive strip	White <input type="checkbox"/>	<b>SAT5</b>	<b>1SNK 900 614 R0000</b>	5 6.00

#### PG5 Mounting Instructions



- Open the PG5-R2 with a flat screwdriver Dia. 3.5 mm 0.138 in ,
- Use a soldering iron to fix your component,
- Close the PG5-R2.