



## PL Protecting Covers

### Terminal Blocks Accessories



#### Features and Benefits

- Prohibit access to the screw clamps,
- Indicate live circuits.

#### Main Technical Data

Material Specifications	Insulating material	Polycarbonate	
	Flammability	V2	
	NF F 16 101		
Ambient temperature min/max	Service IEC 60068-2-1	-55 +110 °C	-67 +230 F
	Storage	-55 +110 °C	-67 +230 F
	Installing	-15 +40 °C	-23 +104 F

#### Ordering Details

##### PL Protecting Covers

Description	Type	Order Code	Pack <sup>(n°)</sup> pieces	Weight g (1 pce)
5.2 mm <i>0.205 in</i> spacing	Transparent <input checked="" type="checkbox"/>	<b>PL5</b>	20	1.50
6 mm <i>0.236 in</i> spacing		<b>PL6</b>	20	1.84
8 mm <i>0.315 in</i> spacing		<b>PL8</b>	20	2.55
10 mm <i>0.394 in</i> spacing		<b>PL10</b>	10	3.13
16 mm <i>0.630 in</i> spacing		<b>PL16</b>	10	4.60

#### PL Mounting Instructions



- The mounting of the PL does not require a screwdriver.
- The dismounting of the PL requires a screwdriver Dia.4 mm *0.160 in*, the screwdriver must be positioned in the cover centered hole.