22.5mm 30.5mm IP65 10A 660VAC



Choose one component from each of the colored sections to assemble a complete switch. For other options or further information please contact EAO Switch directly.

Product Profile

The Series 44 is a high quality switch range that includes pushbuttons, indicators, selectors, mushroom headed switches, key switches, joysticks, double pushbutton switches, potentiometer drives and **Emergency-stops.**

The switches utilize self cleaning slow-make switching elements.

Technical drawings see pages 49-51

- IP65 Protection
- Switch Rating, 10A, 660VAC
- Raised Mounting into 22.5mm cut out
- Flush Mounting into 30.5mm cut out
- Illumination using Ba9s (T-3¹/₄ bayonet base) Lamps or LED's
- Screw terminal connections
- Available as components



O Indicator

Indicator, round, raised, full face with plastic matt chrome bezel, 22.5mm mounting, lamp element included



Indicator, round, raised with plastic matt chrome bezel, 22.5mm mounting, lamp element included

Color	Part No.	Color	Part No.	
Red	44-750.22.000	🔵 Red	44-751.22.000	
O Yellow	44-750.24.000	O Yellow	44-751.24.000	
O Green	44-750.25.000	🔵 Green	44-751.25.000	
O Clear	44-750.27.000	O Clear	44-751.29.000	
For comple	te switch also order Ö	For complete switch also order 🍟		

Illuminated pushbutton

Non-illuminated pushbutton

Non-illuminated raised pushbutton with plastic matt chrome bezel, switch element included. 22.5mm mounting

44-701.22.001 Momentary

44-701.20.100 Momentary

44-702.20.100 Maintained

Action

Contact type

1NC

1N0

1N0

1N0

1NO/NC

1N0/1NC



Illuminated raised pushbutton with plastic matt chrome bezel, switch and lamp element included, 22.5mm mounting

	-	Ũ	
Color	Part No.	Action	Contact type
Red	44-746.22.001	Momentary	1NC
O Yellow	44-746.24.010	Momentary	1N0
🔵 Green	44-746.25.010	Momentary	1N0
O White	44-746.29.100	Momentary	1N0/1NC
🔵 Green	44-747.25.010	Maintained	1NO
O White	44-747.29.100	Maintained	1N0/1NC



Double pushbutton actuator

Double pushbutton actuator with plastic matt chrome bezel, without switch element or contact block holder

Color	Part No.	Markings	Action			
Red/ Green	44-770.2	No markings	Momentary			
Red/ Green	44-771.2	I + 0	Momentary			
Pushbuttons are not interlocked						
	Requires co	ntact/lamp elem	ent holder			
F			č A			

For complete switch also order \widehat{Q}

For complete switch also order 🕢 🍚 🗛

Color

Red

Black

Black

Part No.


Green 44-701.25.010 Momentary

O White 44-701.29.010 Momentary

Green 44-702.25.010 Maintained

22.5mm 30.5mm IP65 10A 660VAC

Series 44




For complete switch also order

For complete switch also order A

Selector switch Mushroom headed pushbutton Joystick Mushroom headed pushbutton, 50mm Selector switch, raised, black lever, Joystick, raised with switch element, 2 and 3 position with plastic matt diameter, plastic matt chrome bezel, without 2, 4 or 8 positions, IP65 chrome bezel, switch element included switching element or contact block holder Positions Drawing Part No. Action Contact type Position Color Part No. Action Part No. Contact type 1 44-720.20.100 Maintained 1N0/1NC 2 🔵 Red 44-707.22 Momentary 44-800.2 2x 1N0/1NC 2 positions 2 44-724.20.020 Maintained 2N0 3 🔵 Green 44-707.25 Momentary 44-800.4 4x 1N0/1NC 4 positions Black 44-707.20 Momentary 44-800.8 4x 1NO/1NC 8 positions Ratings: • 6A/250VAC, 0.5A/250VAC, 2A/110VDC, 5A/75VDC • QC terminals (0.110 x 0.020"), push-on/solder -25°C to 70°C (-13°F to 158°F) Requires contact/lamp element holder >2 million operations in each direction

For complete switch also order 🕢 🗛

22.5mm 30.5mm IP65 10A 660VAC



Choose one component from each of the colored sections to assemble a complete switch. For other options or further information please contact EAO Switch directly.

Potentiometer drive

Switching element



Potentiometer drive (without potentiometer), plastic matt chrome bezel, marked 1-5, for potentiometers with 6mm shafts, IP65




Contact block, screw terminal, slow-make forced opening contacts, stackable



Contact block, screw terminal, slow-make forced opening contacts, non-stackable

Part No.		Part No.	Contact type	Contact material		Part No.	Contact type	Contact material
44-744.20		44-161	1N0	Hard silver		44-121	1N0	Hard silver
		44-151	1NC	Hard silver		44-111	1NC	Hard silver
		44-131	1N0/1NC	Hard silver				
For complete switch also order 🔘 🔘 🔗 🕀 🕕					For comp	lete switch	also order 🔘 (O & L D



A Accessories



LED, BA9s (T-33/4 bayonet base), single chip, 28 Volt and 230 Volt. Also available in 6 Volt, 12 Volt, 24 Volt, 48 Volt and 230 Volt



Lamp element for Ba9s (T-3³/₄ bayonet base) LED/Lamp



Contact/Lamp element holder for double pushbutton actuator and mushroom headed pushbutton

Color	Part No.	Voltage	Part No.	Part No.
Red	10-2513.1142	28VAC/DC, 13mA	44-524	44-902
O Yellow	10-2513.1144	28VAC/DC, 13mA		
O Green	10-2513.1145	28VAC/DC, 7mA		
O Blue	10-2513.1146	28VAC/DC, 13mA		
O White	10-2513.1149	28VAC/DC, 13mA		
🔴 Red	10-2H24.2052	130VAC / 5mA		
O Yellow	10-2H24.2054	130VAC / 5mA		
O Green	10-2H24.2055	130VAC / 3mA		
O Blue	10-2H24.2056	130VAC / 5mA		
O White	10-2H24.2059	130VAC / 5mA		

LED

A

ACCESSORIES


Choose one component from each of the colored sections to assemble a complete switch.

For other options or further information please contact EAO Switch directly.

A Accessories



Front bezel set for 30.5mm flush mount, black plastic, for illuminated pushbutton, selector and keylock



Front bezel set for 30.5mm flush mount with label support, black plastic, for illuminated pushbutton, selector and keylock



Label for front bezel set for 30.5mm flush mount with label support, self adhesive

~

BLOCK

Part No. Product description Color Part No. 44-946.03-A 44-946.04 \into Auminum 44-946 44-946.01-A For potentiometer and indicator only 44-946.02 For potentiometer and indicator only Image: Black	
44-946.01-A For potentiometer and indicator only 44-946.02 For potentiometer and indicator only Black 44-946.0	

A Accessories



Protective cover for raised pushbutton only

Part No.
44-922



22.5mm 30.5mm IP65 10A 660VAC



Choose one component from each of the colored sections to assemble a complete switch. For other options or further information please contact EAO Switch directly.

A Accessories



Emergency-stop switch label, 60mm and 45mm diameter, English, French, German and no markings



Emergency-stop protective shroud, yellow painted alluminium with 22.5mm mounting hole




Mounting tool

English, French, German and no markings		irkings			
	Part No.	Markings	Diameter	Part No.	Part No.
	44-950	No markings	60mm	Contact EAO Switch directly	44-935
	44-950.1	Not Aus	60mm		
	44-950.2	Emergency Stop	60mm		
	44-950.3	Arret D'urgence	60mm		
	44-951	No markings	45mm		
	44-951.1	Not Aus	45mm		
	44-951.2	Emergency Stop	45mm		
	44-951.3	Arret D'urgence	45mm		
	90mm version	ns also available			




44 Indicator

Raised and Flush



44 Pushbutton

Non-Illuminated, Raised





44 Double Pushbutton



Ĩ ЦЦ ДЦ ΠŃ 53 max. lamp element I 92 switching element stackable 1st level e max. 1 switching element not stackable switching element 2nd level 14 _____max.6


44 Pushbutton Mushroom, Double Pushbutton






44 E-Stop

EN 418, EN 418 with Key




44 Keylock

Raised, 2-Position




44 Selector

Raised, 2-Position, 3-Position



44 Potentiometer




for potentiometer No. 44-745

Contact EAO Switch directly


44 Indicator Cut-outs

Raised, Pushbutton Non-Illuminated & Illuminated, 2-Position Keylock, 2 & 3-Position Selector, Potentiometer




44 E-Stop Cut-outs


EN 418, EN 418 with Key, Pushbutton Mushroom



44 Cut-outs, Flush Mounting



44 Double Pushbutton Cut-outs



44 Joystick Cut-outs Contact EAO Switch directly