

Accessories

	Auxiliary Contacts		
	For use with MC10 to MC74		
	Twin bifurcated for low level switching		1 make MCA10
	Rating	AC1 @ 690V 10A	1 break MCA01
		AC15 @ 400V 2A – @ 230V 3A	Early make MCA10U
	Maximum of 4 per contactor		Late break MCA01U
	For use with K3–150 – K3–175 max 1 piece		1M 1B INSIDE HKS11
	For use with K3–150 – K3–175 max 2 pieces		1M 1B OUTSIDE HKS11A
	For use with K3–200 – K3–315 max 3 pieces		1M 1B HKD11
	For use with K3–450 – K3–700 max 1 piece		2M 2B HKF22
Rating	AC1 @ 690V 10A		
	AC15 @ 400V 2A – @230V 3A		
	Electronic Timer		
	For use with MC10 to MC74		Delay-on
	Delay timer with LED indicator		1-30 secs MCT-A30
	Repeat accuracy 1% – Recovery time 50ms		10-180 secs MCT-A180
	Rating AC15 0.75A @ 60V-0.15A @ 250V		30-600 secs MCT-A600
			Delay-off
	Max. inrush 25A – min. switching 5mA		1-30 secs MCT-B30
Delay-on supply 24–60V AC or DC – 100–250V AC or DC		10-180 secs MCT-B180	
Delay-off supply 24–60V AC, 100–120V AC or 200-250V AC		30-600 secs MCT-B600	
	Indicator		
	For use with MC10 to MC74		
	Current indicator		Green (LED) MC-ING
	24–660V AC or DC (voltage drop 2V)		Red (LED) MC-INR
	Voltage indicator		
220 – 415V AC or DC		White (Lamp) MC-UN	
24 – 120V AC or DC		Red (LED) MC-UNR	
	Auxiliary Contacts		
	Interface Relay		
	For use with MC10 to MC74		
Relay to interface with electronic circuits			MC-IM 24V
1 make contact rated 0.75A max 250V AC 30V DC			
	Mechanical Interlock		
	For use with MC10 to MC40		MCI-W
	MC24 to MC74		MCI-X
	K85A22 to K110A22		LG8511
	K3–150A11 to K3–175A11		LG10397H
	K3–200A11		LG10398H
	K3–315A11 to K3–550A22		LG10400H
K3–700A22		LG10402H	
	Coil Suppressor		
	For use with	MC10 to MC22	12–24V AC/DC MC-E24
			24–48V AC/DC MC-E48
			110–230V AC/DC MC-E220
			250–415V AC/DC MC-E380
		MC24 to MC74	12–24V AC/DC VG-MC/24
			24–48V AC/DC VG-MC/48
			110–230V AC/DC VG-MC/250
		250–415V AC/DC VG-MC/415	
	Overload Mounting		
	For separate mounting of overloads		
For use with	U1216	With terminal	U12SM