


3900 Splashproof Metal Lever Switches 16A 250Vac



16(4)A 250Vac T85 (3900 & 3950)
 10(4)A 250Vac T85 (All other circuits)
 UL CSA 20A 125/277Vac (ON-OFF Circuits)
 UL CSA 16A 125/277Vac (Other Circuits)
 UL CSA 7A 72Vdc, 14A 36Vdc
 UL 250Vac 1hp, 125Vac 1/2hp
 UL 85°C, file E45221, CSA file LR10990

Inrush rating - Contact factory for details

Approvals and ratings vary with function
 3mm contact gap except where marked μ
 Integral O-ring neck seal
 Technical data on pages 4 & 5



▶	TERMINAL	FUNCTION		▶	ACTUATOR
C	<p>6.3 x 0.8</p>	Single pole	Double pole	B	
		3900	3950		
		3901	3951		
		3902	3952		
		3910	3960		
S	<p>Screw & clamp available for On - Off switches only</p>	3911	3961		
		3920	3970		
T	<p>Solder</p>	3921	3971		
		3922	3972		
					Finish is nickel plate



C3900BA ---



C3920BA ---



C3950BB ---



C3972BB ---




Guard R17-10



Anti-rotation tab can be specified for guard fitted in On or Off position

BODY

A
Without terminal barrier
Single pole



B
With terminal barrier
Double pole only



Panel hole (all types)

OPTIONS

Neck Seal M539

Actuator is visible



Cover M1080



Covers have internal nylon nuts

Fixing nuts

Nickel plated brass are supplied



Hex Back nut





Knurled Front nut

Panel thickness 4.0 with backnut

DIMENSIONS (mm) * Indicates ON position (for On - Off switches)

Single Pole

(C terminals shown)



Optional
P232 plate
SP or DP

Double Pole

(C terminals shown)

