

























RMQ Titan
Complete Units for Cover Mounting

| | | | | | | Front ring titanium | |
|-------------------------------------------------------------------------------------|--------------------------|-------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------|
| | | | | | | Type | Price |
| | | | | | | Article No. | see price list |
| Button plate | | Color | Contacts | | | | |
| | | | N.O. = normally open N.C. = normally closed ⊕ = Positive opening safety function to IEC/EN 60 947-5-1 | | | | |
| | | | N.O. | N.C. | | | |
| Pushbuttons, IP67, IP69K | | | | | | | |
|  | Flush | START | green | 1 | – |  | M22-D-G-GB1/K10 109420 |
| | | STOP | red | – | 1 ⊕ |  | M22-D-R-GB0/K01 109421 |
| | | START | green | 1 | 1 ⊕ |  | M22-D-G-GB1/K11 109422 |
| | | STOP | red | 1 | 1 ⊕ |  | M22-D-R-GB0/K11 109423 |
|  | Extended | START | green | 1 | – |  | M22-DH-G-GB1/K10 109424 |
| | | STOP | red | – | 1 ⊕ |  | M22-DH-R-GB0/K01 109425 |
| | | START | green | 1 | 1 ⊕ |  | M22-DH-G-GB1/K11 109426 |
| | | STOP | red | 1 | 1 ⊕ |  | M22-DH-R-GB0/K11 109427 |
|  | Mushroom-head | START | green | 1 | – |  | M22-DP-G-GB1/K10 109428 |
| | | STOP | red | – | 1 ⊕ |  | M22-DP-R-GB0/K01 109429 |
| | | START | green | 1 | 1 ⊕ |  | M22-DP-G-GB1/K11 109430 |
| | | STOP | red | 1 | 1 ⊕ |  | M22-DP-R-GB0/K11 109431 |
| Double pushbuttons, IP66 | | | | | | | |
|  | Cover plate, white | START | green | 1 | – |  | M22-DDL-GR-GB1/GB0/K11 109432 |
| | | STOP | red | – | 1 ⊕ |  | |
| With LED element lens white 85 – 264 V AC | START | green | 1 | – |  | M22-DDL-GR-GB1/GB0/K11/230-W 109433 | |
| | STOP | red | – | 1 ⊕ |  | | |
| Selector switches, black thumb-grip handle, IP66 | | | | | | | |
| Maintained/spring-return function can be changed using M22-XC-Y coding adapters | | | | | | | |
|  | Two position, maintained | | 1 | – |  | M22-WKV/K10 109434 | |
| | | | 1 | 1 ⊕ |  | M22-WKV/K11 109435 | |
| Three position, maintained | | 2 | – |  | M22-WRK3/K20 216520 | | |

























Notes

¹⁾ Switch positions 0, I, II correspond to the position of the selector switch viewed from the front.

RMQ Titan
Complete Units for Cover Mounting






















NEMA/UL/CSA 12, 13, 3R, 4X / CE

Pushbuttons and Stacklights

| | | | | | Front ring titanium | |
|----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------|------------------------------------------------------------------------------------|--------------------------|--------------------------|
| Button plate | Color | Contacts | | Type | Price | |
| | | N.O. = normally open N.C. = normally closed ⊖ = Positive opening safety function to IEC/EN 60 947-5-1 | | Article No. | see price list | |
| | | N.O. | N.C. | | | |
| Key-operated selector switches, with 1 key, IP66 | | | | | | |
| Maintained/spring-return function and key withdrawability can be changed using M22-XC... coding adapters | | | | | | |
| Two position, maintained MS1 lock mechanism | | - | 1 ⊖ |  | M22-WRS/K01 109436 | |
|  | | 1 | 1 ⊖ |  | M22-WRS/K11 216517 | |
| | | 2 | - |  | M22-WRS3/K20 109437 | |
| Indicating lights, IP 67, 69K | | | | | | |
| Flush lens, with LED element 85 – 264 V AC |  | green | | | M22-L-G/230-G 109438 | |
| |  | red | | | M22-L-R/230-R 109439 | |
| |  | yellow | | | M22-L-Y/230-W 109440 | |
| |  | white | | | M22-L-W/230-W 109441 | |
| |  | blue | | | M22-L-B/230-B 109442 | |
| | Flush lens, with LED element 12 – 30 V AC/DC |  | green | | | M22-L-G/G 109443 |
|  | | red | | | M22-L-R/R 109444 | |
|  | | yellow | | | M22-L-Y/W 109445 | |
|  | | white | | | M22-L-W/W 109446 | |
|  | | blue | | | M22-L-B/B 109579 | |
| Extended lens, with LED element 85 – 264 V AC | |  | green | | | M22-LH-G/230-G 109447 |
| |  | red | | | M22-LH-R/230-R 109448 | |
| |  | yellow | | | M22-LH-Y/230-W 109449 | |
| |  | white | | | M22-LH-W/230-W 109450 | |
| |  | blue | | | M22-LH-B/230-B 109451 | |
| | Extended lens, with LED element 12 – 30 V AC/DC |  | green | | | M22-LH-G/G 109452 |
|  | | red | | | M22-LH-R/R 109453 | |
|  | | yellow | | | M22-LH-Y/W 109454 | |
|  | | white | | | M22-LH-W/W 109455 | |
|  | | blue | | | M22-LH-B/B 109456 | |

RMQ Titan
Complete Units for Cover Mounting

Pushbuttons and Stacklights

| | | | | | Front ring titanium | |
|----------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|------|-----|-----------------------------------------------------------------------------------|-------------------------------|
| Button plate | Color | Contacts | | | Type | Price |
| | | N.O. = normally open N.C. = normally closed ⊕ = Positive opening safety function to IEC/EN 60 947-5-1 | | | Article No. | see price list |
| | | N.O. | N.C. | | | |
| Illuminated pushbuttons, IP 67, 69K | | | | | | |
| Flush lens, with LED element 85 – 264 V AC |  | green | 1 | 1 ⊕ |  | M22-DL-G/K11/230-G 109457 |
| |  | red | | | | M22-DL-R/K11/230-R 109458 |
| |  | yellow | | | | M22-DL-Y/K11/230-W 109459 |
| |  | white | | | | M22-DL-W/K11/230-W 109460 |
| |  | blue | | | | M22-DL-B/K11/230-B 109461 |
| Flush lens, with LED element 12 – 30 V AC/DC |  | green | | | | M22-DL-G/K11/G 109462 |
| |  | red | | | | M22-DL-R/K11/R 109463 |
| |  | yellow | | | | M22-DL-Y/K11/W 109464 |
| |  | white | | | | M22-DL-W/K11/W 109465 |
| |  | blue | | | | M22-DL-B/K11/B 109466 |
| Extended lens, with LED element 85 – 264 V AC |  | green | | | | M22-DLH-G/K11/230-G 109467 |
| |  | red | | | | M22-DLH-R/K11/230-R 109468 |
| |  | yellow | | | | M22-DLH-Y/K11/230-W 109469 |
| |  | white | | | | M22-DLH-W/K11/230-W 109470 |
| |  | blue | | | | M22-DLH-B/K11/230-B 109471 |
| Extended lens, with LED element 12 – 30 V AC/DC |  | green | | | M22-DLH-G/K11/G 109472 | |
| |  | red | | | M22-DLH-R/K11/R 109473 | |
| |  | yellow | | | M22-DLH-Y/K11/W 109474 | |
| |  | white | | | M22-DLH-W/K11/W 109475 | |
| |  | blue | | | M22-DLH-B/K11/B 109476 | |