



- NOTES**
- 1 THE + MAGNETIC FLUX IS IN THIS DIRECTION (THIS ASSUMES THE CONVENTION THAT THE DIRECTION OF THE EXTERNAL FLUX OF A MAGNET IS FROM THE NORTH TO THE SOUTH POLE OF THE MAGNET)
 - 2 AT 25°C AND 2200 OHM LOAD
 - 3 ABSOLUTE MAXIMUM RATINGS ARE THE EXTREME LIMITS THAT THE DEVICE WILL WITHSTAND WITHOUT DAMAGE TO THE DEVICE. HOWEVER, THE ELECTRICAL AND MAGNETIC CHARACTERISTICS ARE NOT GUARANTEED AS THE MAXIMUM LIMITS (ABOVE RECOMMENDED OPERATING CONDITIONS) ARE APPROACHED NOR WILL THE DEVICE NECESSARILY OPERATE AT ABSOLUTE MAXIMUM RATING
 - 4 REFERENCE CURVES



MAGNETIC CHARACTERISTICS

PARAMETER	PERFORMANCE @ 12 VDC	
	TYPICAL	MAX TOLERANCE
SPAN (-400 TO +400 GAUSS)	6.00 VDC	
NULL (OFFSET AT 0 GAUSS)	6 VDC	±0.6 VDC
SENSITIVITY (MV/GAUSS) (V _O @ 340g - V _O @ -340g) / 680	7.5	±2
LINEARITY % OF SPAN		±1.5%
TEMPERATURE ERROR NULL % OF SPAN -40°C TO 150°C -25°C TO 85°C 0°C TO 50°C		±5% ±3% ±2%
GAIN -40°C TO 0°C 0°C TO 150°C		-0.034%/°C -0.077%/°C

ELECTRICAL CHARACTERISTICS

	24°C	-40°C TO +180°C	REMARKS
SUPPLY CURRENT (MAX)	16 mA	19 mA	EXCLUDING LOAD CURRENT 8 TO 16VDC SUPPLY VOLTAGE

ABSOLUTE MAXIMUM RATING

SUPPLY VOLTAGE	-0.5 TO +18.0 VDC
OUTPUT CURRENT	10 mA MAX
STORAGE TEMPERATURE	-40°C TO 150°C
MAGNETIC FLUX	NO LIMIT, THE CIRCUIT CANNOT BE DAMAGED BY MAGNETIC OVERDRIVE

THIRD ANGLE PROJECTION

SCALE -

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

NO PLACE	(0)	± 0.040
ONE PLACE	(0.0)	± 0.030
TWO PLACE	(0.00)	± 0.015
ANGLES		± -
WEIGHT		

DRAWING NUMBER: 9ISS12-2
 PAGE 1 OF 1
 REV. 18/03
 A 10/70/4
 B 10/70/6
 C 10/70/3
 0038892
 3 MAR 00
 SAV 3 MAR 00
 RASTER

CAUTION
ELECTROSTATIC DISCHARGE
ESD SENSITIVITY: CLASS 2

MASTER REDUCED
ANSI Y14.5M-1982 APPLIES

MICRO SWITCH
a Honeywell Division
FED. REG. COPY #1926

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

SOLID STATE
LINEAR OUTPUT HALL
EFFECT TRANSDUCER

CATALOG LISTING
9ISS12-2