


- NOTES
- SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
  - MICRO SWITCH CATALOG LISTING AND CIRCUIT DESIGNATION MARKED ON SIDE OF SWITCH
  - FURNISHED UNASSEMBLED
  - FOR TERMINAL COVER SEE MICRO SWITCH CATALOG LISTING 5PA9
  - KEYWAY SHOWN ON LEFT SIDE
  - SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE OF TOGGLE LOCKING. SEE CHART FOR AVAILABLE LOCKING COMBINATIONS
  - GOLDE PLATED CONTACTS

CATALOG LISTING		AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERED DETAILS		STYLE NUMBER		CURRENT CAPACITY (AMPS)								
						RESISTIVE LOAD		LAMP LOAD		INDUCTIVE LOAD				
DC VOLTS	AC VOLTS	DC VOLTS	AC VOLTS	DC VOLTS	AC VOLTS	DC VOLTS	AC VOLTS	DC VOLTS	AC VOLTS	DC VOLTS	AC VOLTS			
15A	125, 250, 277 VAC	1/2HP	125 VAC	IRP	250, 277 VAC	5A	125 VAC	"L"						
4TL887-12		NONE		1		20	7.5	5	15	6	5	4	12	15
4TL887-12		A,B,E,L,M,P,D,F,G,H,J,K,N		2										
"A"		"B"		"D"		"E"		"F"		"G"				
LOCKED IN THREE POSITIONS		LOCKED IN CENTER AND EXTREME POS. (KEYWAY SIDE)		LOCKED OUT OF CENTER POSITION		LOCKED IN CENTER POSITION		LOCKED IN EXTREME POS. (OPP. KEYWAY)		LOCKED IN EXTREME POS. (KEYWAY SIDE)				
"H"		"J"		"K"		"L"		"M"		"N"				
LOCKED OUT OF CENTER AND EXTREME POS. (KEYWAY SIDE)		LOCKED OUT OF CENTER AND EXTREME POS. (OPP. KEYWAY)		LOCKED IN CENTER AND EXTREME POS. (OPP. KEYWAY)		LOCKED OUT OF EXTREME POS. (KEYWAY SIDE)		LOCKED OUT OF EXTREME POS. (OPP. KEYWAY)		LOCKED OUT OF EXTREME POS. (OPP. KEYWAY)				
"H"														
LOCKED OUT OF AND INTO EXTREME POS. (KEYWAY SIDE)														
LOCKWASHER		LOCKING RING		2X HEX NUT										
CIRCUIT MADE WITH TOGGLE LEVER IN														
KEYWAY SIDE				CENTER				OPPOSITE KEYWAY						
MAINTAINED POSITION				MAINTAINED POSITION				MAINTAINED POSITION						



STYLE 2 LEVER

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.		
<b>MICRO SWITCH</b> a Honeywell Division	<b>SWITCH - TOGGLE</b>	CATALOG LISTING <b>4TL887-12 SERIES</b> <b>CHART 1</b>
FED. REG. CODE 91329		
THIRD ANGLE PROJECTION		
SCALE FULL		
DO NOT SCALE PRINT		
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		
ONE PLACE (.01) ±.030		
TWO PLACES (.00) ±.015		
THREE PLACES (.000) ±.005		
ANGLES ±		
WEIGHT		

ANSI Y14.5M-1982 APPLIES

PTC/CAD 70  
 3 A V 124 NOV 83  
 JMT 24 1001 93  
 4TL887-12 SERIES CHART 1  
 REV 2  
 1983