


PROFIPOL

Order No.: 1209101

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1209101>

Voltage tester, for DC and AC voltages of 6 V to 400 V, IP65

Commercial data

GTIN (EAN)	 4 046356 309899
sales group	C303
Pack	1 pcs.
Customs tariff	90303310
Catalog page information	Page 648 (CL-2009)

Product notesWEEE/RoHS-compliant since:
08/29/2007

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General**

Color	black
Ambient temperature (operation)	-10 °C ... 55 °C
Degree of protection	IP65
Voltage supply	2 x micro battery 1.5 V, LR03, AAA
Display scope	12 V, 24 V, 50 V, 120 V, 230 V, 400 V AC/DC diode display LED

Phase display	LED
Polarity display	LED (symbol "+/-")
Innenwiderstand_Messkreis	130.00 kΩ
Minimum voltage	6 V DC
Max. voltage	400 V DC
Minimum voltage	6 V AC
Max. voltage	400 V AC

Certificates / Approvals



Certification

VDE-PZI

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;