



NOTE :
 - MARKING "B" IS USED TO IDENTIFY "HP" TERMINAL
 - CRIMPING SPECIFICATION ACCORDING TO CS-64322-001

ISKO COTES CARACTERISTIQUES SPECIALES
 SPECIAL KEY CHARACTERISTICS
 INDICATION DIMENSIONS S.P.C
 DENOTES S.P.C DIMENSIONS
 INDICATION DIMENSIONS CRITIQUES
 DENOTES CRITICAL DIMENSIONS
 INDICATION DIMENSIONS FONCTIONNELLES
 DENOTES FUNCTIONAL DIMENSIONS
 QUANTITE PAR FEUILLE INDIVIDUELLE
 QUANTITY PER INDIVIDUAL SHEET
 1 0 4 ISKO 0

2	BOX TERMINAL	STAINLESS STEEL thickness = 0.15 mm									
1	BODY TERMINAL	HIGH CONDUCTIVITY COPPER ALLOY thickness = 0.2mm									
MARK	DESIGNATION	MATERIAL									
0643221339	Au 127H MINI	Sn	Ni	0.75	2.5	2.4	0.6	3.3	2.8	0.75	0.119
0643221359	Au 127H MINI	Sn	Ni	0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221549	Au 127H MINI	Sn	Ni	0.22 TO 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
MATERIAL NUMBER	CONTACT AREA	CRIMPING AREA	UNDERLAYER	CRIMPING RANGE (mm ²)	A±0.2	B±0.2	C ^{+0.15} _{-0.1}	D±0.2	E±0.2	F±0.1	WEIGHT (g)

Revised Dwg. 2008/05/19 Drawn: JILLOU 2008/05/19 Checked: PAROLARI 2008/05/19 Appr.: LSTICKEIR 2008/05/19	QUALITY SYMBOLS 0.05 0.10 0.20	GENERAL TOLERANCES (UNLESS SPECIFIED) 2 PLACES ±0.10 3 PLACES ±0.15 2 PLACES ±0.10 1 PLACE ±0.1 ANGULAR ± 2°	DIMENSION STYLE MM ONLY DRAWN BY: VGUERIN 2007/04/18 CHECKED BY: PAROLARI 2007/04/19 APPROVED BY: LSTICKEIR 2007/04/20	SCALE 10:1 DESIGN UNITS METRIC FIRST ANGLE PROJECTION	TITLE CP HP RCPT TRM 0.6
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE CHART	DOCUMENT NO. SD-64322-002	SHEET NO. 1 OF 1
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
	MOLEX INCORPORATED				