


MCTE-MRR-V

		REVISIONS						
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Geetha	03/6/08	Suresh	03/6/08	G. C	17/6/08

MCTE-MRR



his data sheet and its contents (the "information") belong to the Pernief Famell Group he "Group") or are licensed to it. No licence is granted for the use of it other than for formation purposes in connection with the products to which it relates. No license any intellectual property rights is granted. The information is subject to change withton to and replaces all data sheets previously supplied. The information supplied is believed to be accurately of the granted property of the property of the property of the sheet of the accuracy of the property of the property of the property of the state sheet should check for themselves the information and the subshilly of the prodtion of the property of TOLERANCES:

UNLESS OTHERWISE
SPECIFIED,
DIMENSIONS ARE
FOR REFERENCE
PURPOSES ONLY.

 DRAWN BY:
 DATE:

 Geetha
 03/06/08

 CHECKED BY:
 DATE:

 Suresh
 03/06/08

 APPROVED BY:
 DATE:

 G.Cook
 17/06/08

Detector Switch - Card

SIZE DWG NO. M10001227 ELECTRONIC FILE TE-MR-V_DWG A


SCALE: NTS U.O.M.: mm (Inches) SHEET: 1 OF 4



MCTE-MRR-V

REVISIONS								
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Geetha	03/6/08	Suresh	03/6/08	G. C	17/6/08

MCTE-MRL



UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

Geetha 03/06/08 CHECKED BY: DATE: Suresh 03/06/08 APPROVED BY: DATE: G.Cook 17/06/08

Detector Switch - Card SIZE DWG NO. M10001227 Α

SCALE: NTS

ELECTRONIC FILE REV TE-MR-V_DWG Α U.O.M.: mm (Inches) SHEET: 2 OF



MCTE-MRR-V

			REVISIONS						
ECN	# RE	EV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	A	А	RELEASED	Geetha	03/6/08	Suresh	03/6/08	G. C	17/6/08

Specifications:

Mechanical:

Maximum operating force : 40gf. Maximum stroke : 2.15mm. Operating temperature : -10°C to +60°C. Storage temperature : -20°C to +70°C.

Electrical:

Electrical life : 50,000 cycles. Rating : 50mA, 20V dc. : 1Ω.

Maximum contact resistance

Minimum insulation resistance : $100M\Omega$ at 100V dc. : 100V ac/1minute. Dielectric strength Contact arrangement : 1 pole 1 throw.

Material:

Cover : Copper alloy, tin plated. Base : High-temperature thermoplastic.

Color : Black.

Stem : High-temperature thermoplastic.

Color : Black.

Contact disc : Stainless with silver cladding. Terminal : Brass with silver plated.

Soldering Process:

For best results, please follow these recommendations:

Hand Soldering : Use a soldering iron of 30 watts, controlled at 608°F (320°C) approximately 2 seconds while applying. Reflow Soldering : When applying reflow soldering, the peak temperature or the reflow oven should be set to 260°C maximum.

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:	DRAWING T		
Geetha	03/06/08]		
CHECKED BY:	DATE:	SIZE	DV	
Suresh	03/06/08	A		
APPROVED BY:	DATE:	<u> </u>		
G.Cook	17/06/08	SCAL	E: NT	


Ε:	DRAWING TITLE:								
8	Detector Switch - Card								
Ξ:	SIZE DWG NO.			ELECTRONIC FILE				REV	
8	Α		I	M10001227	TE-MR-V_DWG				Α
E: 8	SCALE: NTS		U.O.M.: mm (Inches)		SHEET:	3	OF	- 4	



MCTE-MRR-V

		REVISIONS						
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Geetha	03/6/08	Suresh	03/6/08	G. C	17/6/08


Reflow Temperature Profile:



Part Number Table

Description	Part Number			
Switch, Card Detect Right SMD	MCTE-MRR-V			
Switch, Card Detect Left SMD	MCTE-MRL-V			

Part Number Explanation:



Terminal Type
Actuator Direction

: M = S.M.T Type. : R = Side Stem.

Operating Direction Soldering : R = Right Side and L = Left Side. : V = Lead Free Solderable.

http://www.newark.com

http://www.cpc.co.uk

http://www.farnell.com

(the 'Group') or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change with our notice and replaces all data sheets previously supplied. The Information supplied believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it not for any use made of it. Users of this data sheet should check for themselves the information and the suitability of the products for their purpose and not make any assumptions based on information included costs for their purpose and not make any assumptions based on information included used of it finduluting liability resulting from negligence or where the Group was awere of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from 1s negligence.

TOLERANCES:

UNLESS OTHERWISE
SPECIFIED,
DIMENSIONS ARE
FOR REFERENCE
PURPOSES ONLY.

	DRAWN BY:	DATE:	DRAW	NG TITLE:	
	Geetha	03/06/08	1		
	CHECKED BY:	DATE:	SIZE	DWG NO	
	Suresh	03/06/08	A	5	
	APPROVED BY:	DATE:	- 		
	G.Cook	17/06/08	SCAL	E: NTS	
d		-			

			De
size A	DWG NO.	ľ	V11000
SCAL	.E: NTS		U.O.M.:

 Detector Switch - Card

 M10001227
 ELECTRONIC FILE TE-MR-V_DWG
 REV A

 U.O.M.: mm (Inches)
 SHEET: 4 OF 4