













**RMQ Titan**  
Emergency-Stop Buttons, Stop Button

NEMA/UL/CSA 12, 13, 3R, 4X / CE

Pushbuttons and Stacklights







		Contacts N.O. = normally open N.C. = normally closed ⊕ = Positive opening safety function to IEC/EN 60 947-5-1		Color Color of base yellow		Type Article no.	Price See Price List
		N.O.	N.C.	Plunger	Color <sup>1)</sup>		
<b>Complete units for surface mounting, IP66, 69K</b>							
Emergency-Stop pushbuttons, tamper proof to ISO 13 850/EN 418 Pull to release Max. number of contacts that can be used: 3 × M22-(C)K...							
		1	1		● red operator yellow base	M22-PV/KC11/IY-NA 109496	
		-	2		● red operator yellow base	M22-PV/KC02/IY-NA 109497	
<b>Complete units for cover mounting, IP66</b>							
Emergency-Stop pushbuttons, tamper proof to ISO 13 850/EN 418 Pull to release Max. number of contacts that can be used: 4 × M22-(C)K...							
		-	1 ⊕		● red	M22-PV/K01 216515	
		1	1 ⊕		● red	M22-PV/K11 216516	
Emergency-Stop operator		-	-	-	● red	M22-PV 216876	
Stop pushbutton operator		-	-	-	● black	M22S-PV 225528	
Emergency-Stop operator illuminated		-	-	-	● red	M22-PVL 216878	
Stop pushbutton operator illuminated		-	-	-	● black	M22S-PVL 230962	
<b>Emergency-Stop key-release mushroom-head operator, IP66</b>							
With one key	MS1 individual lock mechanisms	-	-	-	● red	M22-PVS 216879	
	MS2 – 20 individual lock mechanisms	-	-	-	● red	M22-PVS-MS* 216880	
							
<b>Emergency-Stop key-release mushroom-head pushbutton to ISO 13 850/EN 418</b>							
With 1 key, MS1 individual lock mechanism		-	1 ⊕		● red	M22-PVS/K01 216514	
							

Notes

<sup>1)</sup> Red = RAL 3000

## RMQ Titan

### Emergency-Stop Labels, Sealable Shroud

	Text	Country identifier (as explanation)	Color	Type Article no.	Price See Price List	
<b>Emergency-Stop labels, IP66</b>						
Black text, 33 × 50 mm						
	Emergency-Stop	GB	yellow	<b>M22-XZK-GB99</b> 216472		
	Arrêt d'urgence	F		<b>M22-XZK-F99</b> 216473		
	Not-Aus	D		<b>M22-XZK-D99</b> 216471		
	EMERGENZA	I		<b>M22-XZK-I99</b> 216474		
	Blank	-		<b>M22-XZK</b> 216470		
	With customized inscription <sup>1)</sup>	-		<b>M22-XZK-*</b> 216479		
50 × 50 mm						
	Four-language	D, GB, F, I	yellow	<b>M22-XYK1</b> 216484		
	Blank	-		<b>M22-XAK</b> 216464		
	Four-language	D, GB, F, I		<b>M22-XAK1</b> 216465		
	Four-language	D, GB, E, POR		<b>M22-XAK2</b> 216466		
	Four-language	D, GB, NL, F		<b>M22-XAK3</b> 216467		
	Four-language	GB, S, SF, DK		<b>M22-XAK4</b> 216468		
	With customized inscription	-		<b>M22-XAK-*</b> 216469		
Ø = 60 mm						
	Four-language	D, GB, F, I			<b>M22-XBK1</b> 216483	
<b>Sealable shroud<sup>2)</sup>, IP65</b>						
				<b>M22-PL-PV</b> 216397		
<b>Protective collar, IP 65</b>						
	yellow plastic			<b>M22-XGPV</b> 231273		

**Notes**

- <sup>1)</sup> Other languages available upon request - please inquire  
Letter height: 5 mm  
Number of lines: max. 2  
Characters per line: max. 7



- <sup>2)</sup> Transparent with collapse point, can be reused after an Emergency-Stop.  
For use with M22(S)-PV, M22-PVL, M22-PVS  
Adjacent holes in the 30 × 50 mm grid, are to be sealed with M22(S)-B blanking plugs.