



<b>Type</b>	■ Switches
<b>Product type</b>	■ Burgess Sealed Limit switch
<b>Dimensions</b>	■ 53.1 x 20.6 x 29.2 mm
<b>Characteristics</b>	<ul style="list-style-type: none"> <li>■ choice of IP54 or IP67 sealed versions</li> <li>■ precise movements and exceptional repeat accuracy</li> <li>■ robust metal housing</li> <li>■ flying lead version available</li> <li>■ long overtravel</li> </ul>
<b>Rating</b>	■ 250 VAC, 15 A max.
<b>Actuators</b>	■ plunger
<b>Approvals/Quality</b>	<ul style="list-style-type: none"> <li>■ UL</li> <li>■ CSA</li> </ul>

## Typical markets

building automation & security , business machines , heating ventilation & air conditioning , industrial equipment & automation , transportation , distribution

## Typical applications

lightings , computer peripheries , central water heating (gas- or oil-fired) , industrial automations , specialist vehicles , international catalog distributors , regional distributors , sales partners , value added distribution partners , market specific distributors

## Preferred range

Partnumber	Terminal	Actuator	Electrical rating @	
			ENEC	UL/CSA
4BR	screw	plunger	VAC A	250 VAC 10 A
4BR/510	screw	plunger	VAC A	250 VAC 10 A
4BR/SH	prewired 0.5M	plunger	VAC A	250 VAC 10 A