



NOTE -
 ▲ - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS
 2 - SUITABLE ONLY FOR APPLICATIONS IMPARTING A RAPID STROKE TO THE SWITCH PLUNGER

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

BZ-2AW822T
 DRAWING NUMBER
 ISSUE 12
 REVISIONS
 A COI6736 G C H 21 DEC 82
 B CO 28424 S R H 26 JAN 71
 C CO-69351-D JWB 16 JUL 91
 D CO-170184-6 G J W 9 MAR 92
 E CO-752048 DAW 1 FEB 94
 CHECK
 S, JAN '63
 DAW
 CHECK
 21 DEC 62
 DRAWN
 FO-50378

CHARACTERISTICS
OPERATING FORCE ----- 8 1/2 OZ MAX
RELEASE FORCE ----- 1 1/2 OZ MIN
DIFFERENTIAL TRAVEL ----- .008 - .030
OVERTRAVEL ----- .094 MIN

ELECTRICAL DATA
CONTACT ARRANGEMENT SEE CIRCUIT DIAGRAM
UNDERWRITERS' LAB. INC. LISTED RATING 15 A-125, 250, OR 480 VAC 1 A-125 VDC; 0.5 A-250 VDC 1/4 HP-125 VAC; 1/2 HP-250 VAC
-L73-

SCALE FULL
DO NOT SCALE PRINT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
ONE PLACE (.0) ±.030
TWO PLACE (.00) ±.015
THREE PLACE (.000) ±.008
ANGLES ±
WEIGHT

