**Quick Link** 

D063

# Photoelectric Sensor Accessories E39-L/E39-R/E39-S



- Brackets enhance mounting flexibility
- Protective mounts fortify sensors against contact damage
- Height adjustable and rotating mounts available



#### **Mounting Brackets**

| Applicable sensor                      | Description                                                                                      | Bracket materials     | Hardware included                                                | Model     |
|----------------------------------------|--------------------------------------------------------------------------------------------------|-----------------------|------------------------------------------------------------------|-----------|
| E3Z, E3Z-B,<br>E3Z-L, E3Z-LS,<br>E3Z-T | Tall L-bracket                                                                                   | 304 stainless steel   | M3x8 slotted/Phillips<br>screws with spring and<br>plain washers | E39-L153  |
|                                        | Standard L-bracket, horizontal                                                                   |                       |                                                                  | E39-L104  |
|                                        | Horizontal mounting bracket, 20-degree angle adjustability                                       |                       |                                                                  | E39-L43   |
|                                        | Compact vertical protective cover bracket                                                        |                       |                                                                  | E39-L142  |
|                                        | Rear mounting vertical L-bracket                                                                 |                       |                                                                  | E39-L44   |
|                                        | Vertical protective cover bracket                                                                | 304 stainless steel   | M3x12 slotted/Phillips                                           | E39-L98   |
|                                        | Short protective cover bracket,<br>5-degree angle adjustability                                  |                       | screws with spring and plain washers                             | E39-L144  |
|                                        | Short post mount for E3S-R6 and E3S-R8                                                           | 304 and XM7 stainless | Post, screws, nut and<br>bolt, holder/bracket                    | E39-L150  |
|                                        | Tall post mount for E3S-R6 and E3S-R8                                                            | steel, PBT            |                                                                  | E39-L151  |
|                                        | Adjustable height and angle bracket for sensors;<br>horizontal mounting rotates every 45 degrees |                       |                                                                  | E39-L93FH |
|                                        | Adjustable height and angle bracket for sensors; vertical mounting rotates every 45 degrees      |                       |                                                                  | E39-L93FV |
|                                        | Adjustable height and angle bracket for sensors; fixed horizontal base mounting                  |                       |                                                                  | E39-L93H  |
|                                        | Adjustable height and angle bracket for sensors; fixed vertical base mounting                    |                       |                                                                  | E39-L93V  |
| E3T                                    | Horizontal L-bracket for E3T-S side view sensors                                                 | 304 stainless steel   | Not provided                                                     | E39-L116  |
|                                        | Vertical L-bracket for E3T-S side view sensors                                                   |                       |                                                                  | E39-L117  |
|                                        | Vertical S-bracket for E3T-S side view sensors                                                   |                       |                                                                  | E39-L118  |
|                                        | Vertical L-bracket for E3T-F flat sensors                                                        |                       |                                                                  | E39-L119  |
|                                        | Vertical S-bracket for E3T-F flat sensors                                                        |                       |                                                                  | E39-L120  |
| E3F2                                   | Mounting block for sensor, screw mount                                                           | Plastic               | M5x32 bolt                                                       | Y92E-B18  |
|                                        | Mounting bracket for sensor, quick access type                                                   | Nickel plated brass   | Not provided                                                     | Y92E-G18S |
| E39-R1 reflector                       | Mounting bracket; M5 threaded stud and nut                                                       | Iron                  | M5 spring washer and nut                                         | E39-L7    |
| E3S-C                                  | L-bracket, vertical                                                                              | 304 stainless steel   | M4x12 hex bolts with<br>spring and plain<br>washers              | E39-L87   |
| E3JK, F3C-AA,<br>F3C-AL                | L-bracket                                                                                        | Zinc-plated iron      | M4x25 Phillips screws                                            | E39-L40   |
| E3JM                                   | L-bracket                                                                                        | Zinc-plated iron      | Not provided                                                     | E39-L53   |

### Mounting Brackets (Continued)

| Applicable sensor    | Description                                                                | Bracket materials   | Hardware included                                         | Model       |
|----------------------|----------------------------------------------------------------------------|---------------------|-----------------------------------------------------------|-------------|
| E3G                  | L-bracket for E3G-R1/E3G-L7                                                | 304 stainless steel | M4x25 slotted/Phillips                                    | E39-L131    |
|                      | L-bracket for rear mounting E3G-R1/E3G-L7                                  |                     | screws with spring and plain washers                      | E39-L132    |
|                      | L-bracket for E3G-MR/E3G-ML, narrow base                                   | 304 stainless steel | M4x35 slotted/Phillips                                    | E39-L135    |
|                      | L-bracket for E3G-MR/E3G-ML                                                |                     | screws with spring and plain washers                      | E39-L136    |
| E3L                  | L-bracket for E3L-2□4-50, E3L-2RC4                                         | Zinc plated iron    | M4x12 hex bolts with<br>spring and plain<br>washers       | E39-L6      |
|                      | L-bracket for E3L-DS50E4-50                                                | Zinc plated iron    | M4x20 hex bolts with spring and plain washers             | E39-L5      |
| E3S-A                | L-bracket for horizontal sensors                                           | 304 stainless steel | M3x12 slotted/Phillips                                    | E39-L69     |
|                      | L-bracket for vertical sensors                                             |                     | screws with spring and plain washers                      | E39-L70     |
| E3C                  | L-bracket for E3C-1 sensing heads (use 2)                                  | Zinc plated iron    | M3x14 Phillips screws<br>with spring and plain<br>washers | E39-L41     |
|                      | L-bracket for E3C-2 (use 2), E3C-DS10, E3C-VS1G,<br>E3C-VS3R sensing heads | Iron, black coating | M3x10 Phillips screws<br>with spring and plain<br>washers | E39-L42     |
|                      | L-bracket with 10 mm slot for E3C-S10                                      | Zinc plated iron    | M2.3x8 Phillips screws                                    | E39-L127-T1 |
|                      | L-bracket with 20 mm slot for E3C-S10                                      |                     | and spring washers                                        | E39-L127-T2 |
|                      | L-bracket with 30 mm slot for E3C-S10                                      |                     |                                                           | E39-L127-T3 |
| E3S-B                | L-bracket for horizontal sensors                                           | Stainless steel     |                                                           | E39-L71     |
|                      | L-bracket for vertical sensors                                             |                     | screw with spring washer                                  | E39-L72     |
| E3HT                 | Mounting block for sensor, screw mount                                     | Plastic             | M4x20 bolt                                                | Y92E-B8     |
| E3JU                 | L-bracket with 90-degree angle adjustability                               | Iron                | Not provided                                              | E39-LU1     |
| E3A2, E3A2-X         | L-bracket                                                                  | Iron                | M5 hex bolts and nuts                                     | E39-L34     |
| E3B2                 | L-bracket with 10-degree angle adjustability                               |                     |                                                           | E39-L35     |
| E3K                  | L-bracket with 90-degree angle adjustability                               | Iron                | 1/4-20 x 0.55 inch hex bolts                              | E39-L37     |
| E3S-VS               | L-bracket for horizontal sensors                                           |                     | M4x12 hex bolts with<br>spring and plain<br>washers       | E39-L2      |
|                      | L-bracket for vertical sensors                                             |                     |                                                           | E39-L6      |
| E3C-V                | L-bracket for sensing heads                                                | Zinc plated iron    | M3x14 Phillips screws<br>with spring and plain<br>washers | E39-L41     |
| E3M-V                | L-bracket with 90-degree angle adjustability                               | 304 stainless steel | el M4x25 slotted/Phillips                                 | E39-L131    |
|                      | L-bracket                                                                  |                     | screws with spring and plain washers                      | E39-L132    |
| E3X-NL               | Bracket for E32-S15 sensing heads, 45-degree angle adjustability           | 430 stainless steel | Not provided                                              | E39-L109    |
| E3NT                 | Universal L-bracket                                                        | Stainless steel     | M5 hex bolts with spring                                  | E39-EL1     |
|                      | L-bracket adapter                                                          |                     | and plain washers                                         | E39-EL2     |
| F3C-AA,<br>F3C-AL    | L-bracket                                                                  | Zinc-plated iron    | M4 nut                                                    | E39-L40     |
| E3G-L                | L-bracket for E3G-L□1/-L□2                                                 | 304 stainless steel | M3x12 slotted/Phillips                                    | E39-L139    |
|                      | L-bracket for E3G-LD5/-LD6                                                 | 7                   | screws                                                    | E39-L140    |
| E3X-DA-S,<br>E3X-MDA | L-bracket                                                                  | 304 stainless steel | Not provided                                              | E39-L143    |
| E3X-DA-N             | L-bracket                                                                  | 7                   |                                                           | E39-L143    |
|                      | L-bracket for water-resistant E3X-DA                                       | -1                  |                                                           | E39-L148    |
| E3X-NA               | L-bracket                                                                  |                     |                                                           | E39-L143    |
|                      | L-bracket for water-resistant E3X-NA                                       | -1                  |                                                           | E39-L148    |
| E3X, E3X-NH,         | L-bracket                                                                  | -1                  |                                                           | E39-L143    |
| E3X-N, E3X-NVC       |                                                                            |                     |                                                           |             |

### Mounting Brackets (Continued)


| Applicable sensor | Description                                                                                                   | Bracket materials   | Hardware included                                                 | Model     |
|-------------------|---------------------------------------------------------------------------------------------------------------|---------------------|-------------------------------------------------------------------|-----------|
| E3S-X3            | L-bracket                                                                                                     | Zinc plated iron    | M4x12 hex bolts with                                              | E39-L6    |
| E3S-R             | L-bracket for horizontal sensors E3S-RS30 and E3S-R1                                                          |                     | spring and plain<br>washers                                       | E39-L2    |
|                   | L-bracket for vertical sensors E3S-RS30 and E3S-R1                                                            |                     | washers                                                           | E39-L6    |
|                   | L-bracket for horizontal E3S-R1 and E3S-R3                                                                    |                     | M3x12 slotted/Phillips<br>screws with spring and<br>plain washers | E39-L69   |
|                   | L-bracket for vertical E3S-R1 and E3S-R3                                                                      |                     |                                                                   | E39-L70   |
|                   | Horizontal protective cover bracket for E3S-R1 and E3S-R3                                                     | 304 stainless steel | M3x12 slotted/Phillips<br>screws with spring and<br>plain washers | E39-L97   |
|                   | Vertical protective cover bracket for E3S-R6 and E3S-R8                                                       |                     |                                                                   | E39-L98   |
|                   | Adjustable height and angle bracket for E3S-R1/R3/R6/R8 sensors; horizontal mounting rotates every 45 degrees | steel, PBT          | Post, screws, nut and<br>bolt, holder/bracket                     | E39-L93FH |
|                   | Adjustable height and angle bracket for E3S-R1/R3/R6/R8 sensors; vertical mounting rotates every 45 degrees   |                     |                                                                   | E39-L93FV |
|                   | Adjustable height and angle bracket for E3S-R1/R3/R6/R8 sensors; fixed horizontal base mounting               |                     |                                                                   | E39-L93H  |
|                   | Adjustable height and angle bracket for E3S-R1/R3/R6/R8 sensors; fixed vertical base mounting                 |                     |                                                                   | E39-L93V  |
|                   | Short post mount for E3S-R6 and E3S-R8                                                                        |                     |                                                                   | E39-L150  |
|                   | Tall post mount for E3S-R6 and E3S-R8                                                                         |                     |                                                                   | E39-L151  |
| E3S-CR62/66       | L-bracket                                                                                                     | 304 stainless steel | M4x12 hex bolts with                                              | E39-L87   |
| E3S-CD63/68       | L-bracket, ±20 degree angle adjustment                                                                        |                     | spring and plain<br>washers                                       | E39-L113  |
| F3UV              | L-bracket for F3UV-A amplifier                                                                                | 304 stainless steel | M3x25 slotted/Phillips<br>screws, plain washer                    | F39-L9    |
| E3C-T1            | L-bracket for amplifier                                                                                       | 304 stainless steel | Not provided                                                      | E39-L143  |

#### E39-L/E39-R/E39-S Photoelectric Sensor Accessories

#### OMRON

#### Reflectors

- Corner cube reflectors return maximum light back to the sensor receiver
- Reflectors extend or shorten sensing distance to match installation needs
- Hard acrylic reflectors are backed by ABS plastic
- Easy-to-apply, adhesive-backed reflectors are ultra-thin to save space



# Hard Acrylic Reflectors

| Appearance | Dimensions<br>H x W x D mm | Compatible sensors                                  | Directional angle                          | Model             |
|------------|----------------------------|-----------------------------------------------------|--------------------------------------------|-------------------|
|            | 59.9 x 40.3 x 7.5          | E3Z, E3F2, E3JK, E3JM, E3S-CR,<br>E3S-A, E3G, E3S-R | 30° min.;<br>40° with E3JK-R<br>and E3JM-R | E39-R1<br>E39-R1S |
|            | 59.9 H x 80.8 W x 7.5 D    | E3Z, E3F2, E3JK, E3JM,<br>E3S-CR, E3G               | 30° min.;<br>40° with E3G-R                | E39-R2            |
|            | 38 H x 22.5 W x 11 D       | E3Z, E3JK, E3JM,<br>E3S-CR, E3S-A                   | 30° min.                                   | E39-R3            |
|            | 23 H x 13.7 W x 4.9 D      | E3T, E3S-CR, E3S-A                                  | 2° to 20° min.                             | E39-R4            |
|            | 50 x 40 x 4.8              | E3S-CR62/E3S-CR68                                   | 30° min.                                   | E39-R6            |

#### OMRON

### Hard Acrylic Reflectors (Continued)

| Appearance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Dimensions<br>H x W x D mm | Compatible sensors | Directional angle | Model   |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|--------------------|-------------------|---------|
| And the base of the transmission of the transm | 84 dia. x 7.4              | E3F2               | 30° min.          | E39-R7  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 100 x 100 x 9              | E3F2               | 30° min.          | E39-R8  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 42.3 H x 30.9 W x 8 D      | E3Z                | 30° min.          | E39-R9  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 61.4 H x 51.6 W x 8 D      | E3Z                | 30° min.          | E39-R10 |
| 0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 23 H x 13.7 W x 1.1 D      | E3T                | 30° min.          | E39-R37 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 84.5 x 84.5 x 8.7          | E3F2               | 30° min.          | E39-R40 |

### **Adhesive-Backed Tape Reflectors**

| Appearance | Dimensions<br>H x W x D mm | Compatible sensors    | Directional angle | Model   |
|------------|----------------------------|-----------------------|-------------------|---------|
|            | 10 H x 35 W x 0.6 D        | E3Z, E3JK, E3JM       | 30° min.          | E39-RS1 |
|            | 35 H x 40 W x 0.6 D        | E3Z, E3JK, E3JM       | 30° min.          | E39-RS2 |
|            | 70 H x 80 W x 0.6 D        | E3Z, E3F2, E3JK, E3JM | 30° min.          | E39-RS3 |
|            | 10 x 35 x 0.7              | E3F2, E3S-CR, E3S-A   | 30° min.          | E39-RSA |
|            | 35 x 40 x 0.7              | E3F2, E3S-CR, E3S-A   | 30° min.          | E39-RSB |

# Terms and Conditions of Sale

- Offer: Acceptance. These terms and conditions (these "Terms") are deemed part of all quotes, agreements, purchase orders, acknowledgments, price lists, catalogs, manuals, brochures and other documents, whether electronic or in writing, relating to the sale of products or services (collectively, the "<u>Products</u>") by Omron Electronics LLC and its subsidiary companies ("<u>Omron</u>"). Omron objects to any terms or conditions proposed in Buyer's purchase order or other
- documents which are inconsistent with, or in addition to these Terms. <u>Prices: Payment Terms.</u> All prices stated are current, subject to change with-out notice by Omron. Omron reserves the right to increase or decrease prices 2. on any unshipped portions of outstanding orders. Payments for Products are due net 30 days unless otherwise stated in the invoice.
- Discounts. Cash discounts, if any, will apply only on the net amount of invoices sent to Buyer after deducting transportation charges, taxes and duties, and will be allowed only if (i) the invoice is paid according to Omron's payment terms З.
- and (ii) Buyer has no past due amounts. Interest. Omron, at its option, may charge Buyer 1-1/2% interest per month or the maximum legal rate, whichever is less, on any balance not paid within the 4 stated terms
- Orders. Omron will accept no order less than \$200 net billing.
- Governmental Approvals. Buyer shall be responsible for, and shall bear all 6 costs involved in, obtaining any government approvals required for the impor-tation or sale of the Products.
- Taxes. All taxes, duties and other governmental charges (other than general real property and income taxes), including any interest or penalties thereon, imposed directly or indirectly on Omron or required to be collected directly or 7. indirectly by Omron for the manufacture, production, sale, delivery, importa-tion, consumption or use of the Products sold hereunder (including customs duties and sales, excise, use, turnover and license taxes) shall be charged to and remitted by Buyer to Omron.
- Financial. If the financial position of Buyer at any time becomes unsatisfactory 8. to Omron, Omron reserves the right to stop shipments or require satisfactory security or payment in advance. If Buyer fails to make payment or otherwise secondly with these Terms or any related agreement, Omron may (without liabil-ity and in addition to other remedies) cancel any unshipped portion of Prod-ucts sold hereunder and stop any Products in transit until Buyer pays all amounts, including amounts payable hereunder, whether or not then due, which are owing to it by Buyer. Buyer shall in any event remain liable for all unpaid ecounts. unpaid accounts.
- Cancellation; Etc. Orders are not subject to rescheduling or cancellation unless Buyer indemnifies Omron against all related costs or expenses.
- 10. Force Majeure. Omron shall not be liable for any delay or failure in delivery resulting from causes beyond its control, including earthquakes, fires, floods, strikes or other labor disputes, shortage of labor or materials, accidents to machinery, acts of sabotage, riots, delay in or lack of transportation or the requirements of any government authority.
- <u>Shipping: Delivery</u> Unless otherwise expressly agreed in writing by Omron:
  a. Shipments shall be by a carrier selected by Omron; Omron will not drop ship except in "break down" situations.
  - b. Such carrier shall act as the agent of Buyer and delivery to such carrier shall constitute delivery to Buyer; c. All sales and shipments of Products shall be FOB shipping point (unless of
  - erwise stated in writing by Omron), at which point title and risk of loss shall pass from Omron to Buyer; provided that Omron shall retain a security interest in the Products until the full purchase price is paid; d. Delivery and shipping dates are estimates only; and e. Omron will package Products as it deems proper for protection against nor-
- and handling and extra charges apply to special conditions.
  <u>Claims</u>. Any claim by Buyer against Omron for shortage or damage to the Products occurring before delivery to the carrier must be presented in writing to Omron within 30 days of receipt of shipment and include the original trans-portation bill signed by the carrier noting that the carrier received the Products from Omron in the candition claims of the products of the product of the products of the product of the from Omron in the condition claimed.
- Warranties. (a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed 13 (b) <u>Limitations</u>. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABIL-

## Certain Precautions on Specifications and Use

- Suitability of Use. Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, 1. Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases but the following is a (i) Outdoor use, uses involving potential chemical contamination must be given:
   (ii) Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document.

 (ii) Use in consumer products or any use in significant quantities.
 (iii) Energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equip-(iv) Systems, machines and equipment that could present a risk to life or prop-erty. Please know and observe all prohibitions of use applicable to this Product

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO

ITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. Omron further disclaims all warranties and responsibility of IN ISNDED USE. Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or oth-erwise of any intellectual property right. (c) <u>Buyer Remedy</u>. Omron's sole obli-gation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsi-ble for warapty consisting the non-the complex of the non-complying Product the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Compa-nies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty See http://oeweb.omron.com or contact your Omron representative for published information

- lished information. Limitation on Liability: Etc. OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY. Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted. Indemnities. Buyer shall indemnify and hold harmless Omron Companies and their employees from and against all liabilities, losses, claims, costs and expenses (including attorney's fees and expenses) related to any claim inves-
- 15 expenses (including attorney's fees and expenses) related to any claim, inves-tigation, litigation or proceeding (whether or not Omron is a party) which arises or is alleged to arise from Buyer's acts or omissions under these Terms or in any way with respect to the Products. Without limiting the foregoing, Buyer (at its own expense) shall indemnify and hold harmless Omron and defend or setthe any action brought against such Companies to the extent based on a claim that any Product made to Buyer specifications infringed intellectual property
- that any Product made to buyer specifications immiged interfectual property rights of another party. <u>Property: Confidentiality.</u> Any intellectual property in the Products is the exclusive property of Omron Companies and Buyer shall not attempt to duplicate it in any way without the written permission of Omron. Notwithstanding any charges to Buyer for engineering or tooling, all engineering and tooling shall remain the exclusive property of Omron. All information and materials supplied to the Products are confidential and proprietary. 16 by Omron to Buyer relating to the Products are confidential and proprietary, and Buyer shall limit distribution thereof to its trusted employees and strictly
- Export Controls. Buyer shall comply with all applicable laws, regulations and licenses regarding (i) export of products or information; (iii) sale of products to 17 "forbidden" or other proscribed persons; and (ii) disclosure to non-citizens of regulated technology or information. <u>Miscellaneous</u>. (a) <u>Waiver</u>. No failure or delay by Omron in exercising any right
- 18 <u>Miscellaneous</u>. (a) <u>Waiver</u>. No failure or delay by Omron in exercising any right and no course of dealing between Buyer and Omron shall operate as a waiver of rights by Omron. (b) <u>Assignment</u>. Buyer may not assign its rights hereunder without Omron's written consent. (c) <u>Law</u>. These Terms are governed by the law of the jurisdiction of the home office of the Omron company from which Buyer is purchasing the Products (without regard to conflict of law princi-ples). (d) <u>Amendment</u>. These Terms constitute the entire agreement between Buyer and Omron relating to the Products, and no provision may be changed or waived unless in writing signed by the parties. (e) <u>Severability</u>. If any provi-sion hereof is rendered ineffective or invalid, such provision shall not invalidate any other provision. (f) <u>Setoff</u>. Buyer shall have no right to set off any amounts against the amount owing in respect of this invoice. (a) Definitions. As used against the amount owing in respect of this invoice. (g) <u>Definitions</u>. As used herein, "<u>including</u>" means "including without limitation"; and "<u>Omron Compa-nies" (or similar words) mean Omron Corporation and any direct or indirect</u> subsidiary or affiliate thereof.

ADDRESS THE RISKS, AND THAT THE OMRON'S PRODUCT IS PROP-ERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

- 2.
- Programmable Products. Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof. <u>Performance Data</u>. Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitabil-ity and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application require-ments. Actual performance is subject to the Omron's Warranty and Limitations of Linbility. 3. of Liability.
- <u>Change in Specifications</u>. Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our pracchanged at any time based on improvements and other reasons. It is our prac-tice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifica-tions of the Product may be changed without any notice. When in doubt, spe-cial part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product. <u>Errors and Omissions</u>. Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clarical typographical or proofreading errors or omissions.
- for clerical, typographical or proofreading errors or omissions.

Complete "Terms and Conditions of Sale" for product purchase and use are on Omron's website at www.omron.com/oei – under the "About Us" tab, in the Legal Matters section.

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS. To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

# 

#### **OMRON ELECTRONICS LLC**

1 Commerce Drive Schaumburg, IL 60173 Tel: 847.843.7900 For U.S. technical support or other inquiries: 800.556.6766

#### **OMRON CANADA, INC.**

885 Milner Avenue Toronto, Ontario M1B 5V8 Tel: 416.286.6465

#### **MEXICO SALES OFFICES**

Mexico, D.F. 555.660.3144 Ciudad Juárez 656.623.7083 Monterrey, N.L. 818.377.4281 Querétaro 442.135.4510 **BRAZIL SALES OFFICE** Sao Paulo 55.11.2101.6310 **ARGENTINA SALES OFFICE** Cono Sur 54.114.787.1129 **CHILE SALES OFFICE** Santiago 562.206.4592 **OTHER LATIN AMERICAN SALES** Florida 954.227.2121

#### **OMRON ON-LINE**

Global www.omron.com USA -

www.omron.com/oei

Canada www.omron.ca

Brazil www.omron.com.br

Latin America www.espanol.omron.com

Cat. No. X302-E3-01

3/06

Specifications subject to change without notice

Printed in USA