

4, 5 and 8-Wire M12 *eurofast*® Field Wireable Connectors, Standard and Reverse Key

- Straight Female Connectors
- IEC IP 67 Protection



| Drawing | Part Number | Housing Specs. | Application | Pinout |
|---------|----------------|---|---|--------|
| | B 8141-0 | PBT, Black PG 7 cable gland accepts 4-6 mm cable diameter Screw terminals accepts up to 18 AWG conductors 85°C 60 V, 4 A | Mates with <u>standard key 4-pin cordsets and receptacles</u> | |
| | B 8141-0/PG 9 | PBT, Black PG 9 cable gland accepts 6-8 mm cable diameter Screw terminals accepts up to 18 AWG conductors 85°C 60 V, 4 A | Mates with <u>standard key 4-pin cordsets and receptacles</u> | |
| | B 8151-0/PG 9 | PBT, Black PG 9 cable gland accepts 6-8 mm cable diameter Screw terminals accepts up to 18 AWG conductors 85°C 60 V, 4 A | Mates with <u>standard key 5-pin cordsets and receptacles</u> | |
| | BM 8151-0/PG 9 | PBT, Black PG 9 cable gland accepts 6-8 mm cable diameter Screw terminals Metal Coupling Nut 85°C 125 V, 4 A | Mates with <u>standard key 5-pin cordsets and receptacles</u> | |
| | BWS 8141-0 | PBT, Black PG 9 cable gland accepts 6-8 mm cable diameter Screw terminals accepts up to 18 AWG conductors 85°C 250 V, 4 A | Mates with <u>reverse key 4-pin cordsets and receptacles</u> | |
| | BWS 8151-0 | PBT, Black PG 9 cable gland accepts 6-8 mm cable diameter Screw terminals accepts up to 18 AWG conductors 85°C 125 V, 4 A | Mates with <u>reverse key 5-pin cordsets and receptacles</u> | |
| | B 8181-0 | Nylon, Black PG 9 cable gland accepts 6-8 mm cable diameter Screw terminals accepts up to 18 AWG conductors 85°C 30 VAC/75 VDC, 2 A | Mates with <u>standard key 8-pin cordsets and receptacles</u> | |