

## 3 and 4-Pin *minifast*® Field Wireable Connectors

- Straight Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection



Drawing	Part Number	Specs	Application	Pinout
<p>BS 41 ..</p> <p>Ø1.065 [27.0]</p> <p>3.465 [88.0] APPROX</p> <p>7/8-16UN</p>	BS 4131-0/9	Glass filled nylon PG 9 cable gland, accepts 6-8 mm cable diameter Screw terminals, accepts up to 16 AWG conductors 85° C 250 V, 12 A	<i>Mates with all 3-pin cordsets and receptacles</i>	
	BS 4131-0/13.5	Glass filled nylon PG 13.5 cable gland, accepts 10-12 mm cable diameter Screw terminals, accepts up to 16 AWG conductors 85° C 250 V, 12 A	<i>Mates with all 3-pin cordsets and receptacles</i>	
	BS 4141-0/9	Glass filled nylon PG 9 cable gland, accepts 6-8 mm cable diameter Screw terminals, accepts up to 16 AWG conductors 85° C 250 V, 9 A	<i>Mates with all 4-pin cordsets and receptacles</i>	
	BS 4141-0/13.5	Glass filled nylon PG 13.5 cable gland, accepts 10-12 mm cable diameter Screw terminals, accepts up to 16 AWG conductors 85° C 250 V, 9 A	<i>Mates with all 4-pin cordsets and receptacles</i>	