



## Platinum - 600℃ MiniSens

# The World's Smallest Platinum Thin-Film Temperature Sensor




### **Product**

In the combination of sensor knowledge and advanced production technology, we have succeeded in producing the smallest platinum thin-film temperature sensors in the world. The sensors are available in basic values of 100, 500 and 1000 ohms and applicable to temperature range of -200°C to +400°C and +600°C. The miniaturised design opens up totally new applications in temperature measurement and is characterised by many advantages. The chip dimensions of 1,6 x 1,2 mm (length x width) are available on the basis value of 100, 500 and 1000 ohms at DIN EN 60751 tolerance class or better.

#### **Advantages**

- Extremely short response time
- Thanks to its small dimensions, there is space for it anywhere
- More accurate measurements through low heat transfer
- Precise spot measurements on objects
- Excellent long term stability
- Simple interchangeability
- Wide temperature range
- Vibration resistant



#### **Technical Data**

Nominal resistance:  $PT100\Omega$ ,  $PT500\Omega$ ,  $PT1000\Omega$ 

Temperature range: -200℃ to +600℃

Classes: 1/3 DIN class B; DIN class A; DIN class B

Tolerance classes: ½ DIN class B: -50℃ to 150℃

DIN class A: -90℃ to 300℃ DIN class B: -200℃ to 600℃

Temperature coefficient: TCR = 3850ppm/K
Dependence of Resistivity: DIN EN 60751

Wires: Pt-Ni clad wire, Ø 0.2 mm

Long-term stability: max. Drift = 0.03% after 1000h at 600℃

Response time: Water (0.4 m/s) :  $T_{0.63} = 0.08 \text{ s}$ Air (1m/s) :  $T_{0.63} = 1.2 \text{ s}$ 

Measuring current:  $0.5\text{mA} (100 \Omega)$ ;  $0.4\text{mA} (500 \Omega)$ ;  $0.3\text{mA} (1000 \Omega)$ 

Self heating: Water [mW/ $\mathbb{C}$ ]: 12

Air [mW/℃]: 1.8

Other Chipsizes, Nominal resistances, tolerances, length of wire or materials on request.



