


Part Number: SL08 50002

Ordering Different Lead Types:

| | |
|----------------------|---------------------------------------|
| Inside Kinked Leads | Use -A after Ametherm's part # |
| Outside Kinked Leads | Not Available |

For example: to order an inside kinked lead use part number SL08 50002-A



Electrical Specifications:

| | |
|---|-------------------------|
| Resistance @ 25°C | 50.0 Ω \pm 20% |
| Max Steady State Current Up to 65°C | 2.0 A |
| Max Recommended Energy Rating (Joules) | 8.0 J |
| Actual Failure Point of Instantaneous Energy (Joules) | 16.0 J |
| Resistance @ 100% of Max Current | 0.63 Ω |
| Resistance @ 50% of Max Current | 1.10 Ω |
| Body Temperature @ 100% Current Rating | 134 °C |
| Dissipation Constant | 9.0 mW/°C |
| Thermal Time Constant | 20 seconds |

Mechanical Specifications:

| | |
|------------------------------------|--------------------|
| D | 8.0 \pm 0.5 mm |
| T | 4.0 \pm 0.5 mm |
| Lead Diameter | 0.5 \pm 0.1 mm |
| S | 6.4 \pm 2.0 mm |
| L | 38.0 \pm 3.0 mm |
| Straight Leads Coating Run Down | 5.0 \pm 1.0 mm |
| B | 11.5 \pm 3.50 mm |
| C | 2.20 \pm 0.2 mm |