

Part Number: SL15 10006-03

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL15 10006-03-A



### Electrical Specifications:

Resistance @ 25°C	10.0 Ω ± 20%
Max Steady State Current Up to 65°C	6.0 A
Max Recommended Energy Rating (Joules)	55.0 J
Actual Failure Point of Instantaneous Energy (Joules)	100.0J
Resistance @ 100% of Max Current	0.170 Ω
Resistance @ 50% of Max Current	0.388 Ω
Body Temperature @ 100% Current Rating	152 °C
Dissipation Constant	15.9mW/°C
Thermal Time Constant	54 seconds
Material Type	"G"
Max Recommended Voltage	265 VRMS
Max Recommended Capacitance @ 265 VRMS	780μF

### Mechanical Specifications:

D	15.0 ± 0.5 mm
T	8.9 mm Max
Lead Diameter	1.02 ± 0.08 mm
S	7.8 mm Nom
L	38.0 ± 9.0 mm
Inside Kink Dimension	6.35 ± 0.60 mm
B	7.50 ± 0.70 mm
C	2.82 ± 0.5 mm
Coating Run Down on the Straight Leads	5.00 ± 0.5 mm