02

## INSTALLATION FITTINGS FOR TEMPERATURE PROBES

## **FLANGE PLATES**

Labfacility flange plates enable the mounting of temperature probes with compression fittings. Available in stainless steel and brass, flange plates are particularly recommended for mounting probes in process ovens, kilns, heating and ventilating ducts. etc

Diameter

50mm


Female thread

1/8" BSPP

Mounting holes

3 × 4mm dia. on 40mm PCD

ORDER CODES				
STAINLESS STEEL	CA-250			
BRA\$5	CA-251			




## **BAYONET FITTINGS AND ADAPTORS**

Labfacility offers a range of bayonet fittings and associated adaptors for securing temperature sensors. When fitted, a bayonet fitting spring loads the sensor to keep it in permanent contact with the measured surface. Bayonet fittings are particularly suitable for mounting sensors in plastics extruders, injection moulding machines, etc.


Two types of bayonet fixing are available (compression or grub screw). Select the fitting to suit sensor diameter. Adaptors are available in two thread sizes and various lengths.

ORDER CODES - BAYONET FITTINGS				
TYPE	FITTING	PROBE DIA. (mm)	ORDER CODE	
Single slot cap	Compression	3.0	CA-300	
Single slot cap	Compression	4 5	CA-301	
Single slot cap	Grub screw	3.0	CA-302	
Single slot cap	Grub screw	4.5	CA-303	
Twin slot cap	Grub screw	6.0	CA-304	

ORD	ER CODES - A	DAPTORS	
THREAD SIZE	OVERALL LENGTH (mm)	PINS	ORDER CODE
1/8" BSP	22	Single	CA-400
1/8" BSP	35	Single	CA-401
1/8" BSP	48	5ingle	CA-402
1/8" BSP	64	Single	CA-403
1/8" BSP	22	Double	CA-404
M10 × 1mm	35	Single	CA-405



Specifications may be subject to change



Tel: 0181 943 5331 Fax: 0181 943 4351