



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS			DDC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398					
DCP #	RE∨	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPR∨I	DATE
2070	Α	Released	JN	09-03-09	JWM	09-03-09	JWM	09-03-09







Specification

1. Resonant Frequency: 2.6±0.5 KHz

2. Resonant Resistance: 350Ω max.

3. Capacitance: 25000pF±30% at 100Hz

4. Input Voltage: 30 Vp-p max

5. Operating Temperature: -20~+60°C

6. Storage Temperature: -20~+70°C

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:
UNLESS OTHERWISE
SPECIFIED,
DIMENSIONS ARE
FOR REFERENCE
PURPOSES ONLY.

DRAWN BY:	DATE:		
Jason Nash	09-03-09		
CHECKED BY:	DATE:		
Jason Nash	09-03-09		
APPROVED BY:	DATE:		
loson Nosh	U8-U3-U9		

)	DRAW	'ING TITLE:										
09	Piezo-element											
	SIZE DWG. ND.			ELEC	REV							
09	Α	MCFT-36T-2.6A1-139			25R0588.dwg							
.: 09	SCALE: NTS		U		SHEET:	1 [JF 1					