



SPECIFICATION

1. Rated Voltage 12Vp-p Square Wave
2. Max. Allowable Voltage 25Vp-p Square Wave
3. Max. Rated Current 2mA at 4.0KHz/12Vp-p Square Wave
4. Resonant Frequency 4.0±0.5KHz
5. Min. Sound Pressure Level..... 75dB at 4.0KHz/12Vp-p Square Wave/10cm
6. Capacitance at 120Hz 15000pF±30%
7. Case Material ABS
8. Operating Temperature -20 ~ +60°C
9. Store Temperature -30 ~ +70°C
10. Weight 1.3g

		KEPO KEPO ELECTRONIC CO., LTD. http://www.kepo.com.tw	
		Piezo Transducer KPR-1440	
<small>NO.</small>	<small>DESCRIPTION</small>	<small>APPROVED</small>	<small>DATE</small>
<small>DATE AND QUANTITY NOTED OTHERWISE</small>	<small>DRAWN</small>	<small>APPROVALS</small>	<small>DATE</small>
<small>1X = 2X = 3X =</small>	<small>CHECKED</small>		<small>UNIT</small>
<small>90° FURROW 2° SHOULDER 4°</small>	<small>APPROVED</small>		<small>mm</small> <small>DWG NO</small> K P3.840.303
<small>FIRST ANGLE PROJECTION</small>		<small>05.01.28</small>	<small>SCALE</small> <small>SHEET</small> <small>VER</small> 1.0