



SPECIFICATION

1. Rated Voltage12Vp-p Square Wave
2. Max. Allowable Voltage30Vp-p Square Wave
3. Max. Rated Current5mA at 2.8KHz/12Vp-p Square Wave
4. Min. Sound Pressure Level.....85dB at 2.8KHz/12Vp-p Square Wave/30cm
5. Capacitance at 120Hz35000pF±30%
6. Resonant Frequency2.8±0.5KHz
7. Case Material.....ABS
8. Operating Temperature-20~+60°C
9. Store Temperature-30~+70°C
10. Weight10g

| | | | | | |
|---|-------------|-----------|----------|---|--------------|
| | | | | KEPO KEPO ELECTRONIC CO., LTD. http://www.kepo.com.tw | |
| No. | DESCRIPTION | APPROVED | DATE | Piezo transducer KPR-4210 | |
| <small>DISCREPANCIES UNLESS NOTED OTHERWISE</small> X + XX + XXX + 90° FORMED ±° ANGLES ±° | | APPROVALS | DATE | UNIT | DWG NO. |
| FIRST ANGLE PROJECTION | | CHECKED | | mm | KP3.840.325 |
| | | APPROVED | 03.03.26 | SCALE | NOT TO SCALE |
| | | | | SHEET | VER 1.0 |