



Specifications

1. Rated Voltage.....12Vp-p Square Wave
2. Max. Allowable Voltage.....30Vp-p Square Wave
3. Max. Rated Current.....4mA at 1.0KHz/12Vp-p Square Wave
4. Min. Sound Pressure Level..... 80dB at 1.0KHz/12Vp-p Square Wave/30cm
5. Resonant Frequency.....1.0±0.5KHz
6. Capacitance at 120Hz.....66000pF±30%
7. Case Material.....ABS
8. Operating Temperature.....-20~+60°C
9. Store Temperature.....-30~+70°C
10. Weight.....10g

				KEPO KEPO ELECTRONIC CO., LTD. http://www.kepo.com.tw	
				Piezo Transducer KPR-4420G	
No.	DESCRIPTION	APPROVED	DATE	UNIT	DWG NO.
				mm	KP3.840.340
<small>10% JEANSON LINE</small> <small>NOTED OTHERWAYS</small> <small>X</small> <small>XX</small> <small>XXX</small> <small>90° FORMED ±2°</small> <small>ANGLES ±1°</small> <small>FIRST ANGLE PROJECTION</small>		DRAWN	CHECKED	APPROVED	02.12.27
				SCALE	NOT TO SCALE
				SHEET	VER 1.0