


ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.


ILCIIIIOLOGI.			


		RE∨ISI□NS	DOC. NO	1. SPC-F005	* Effe	ctive: 7/8/	02 * D	CP No: 1398
DCP #	RE∨	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPR∨I	DATE
2070	Α	Released	JN	09-03-09	JWM	09-03-09	JWM	09-03-09





SPC-F005.DWG





Specification

1. Rated Voltage: 1.5V

2. Operating Voltage: 1~2V 3. Max. Rated Current: 10mA

4. Coil Resistance: $42\pm6\Omega$ 5. Coil Impedance: 120Ω

6. Min. Sound Pressure Level: 70dB/ 10cm

7. Resonant Frequency: 2048 Hz

8. Case Material/ Color: MPPO/ Black

9. Operating Temperature: -20~+70°C

10. Store Temperature: -30~+80°C

11 Weight: 2g

DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED
HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE
BELIEVE TO BE ACCURATE AND RELIABLE. SINCE
CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE
USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT
FOR THE INTENDED USE AND ASSUME ALL RISK AND
LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:	DRAW			
Jason Nash	09-03-09			М	
CHECKED BY:	DATE:	SIZE	DWG. N□.		
Jason Nash	09-03-09		MCKP12-G	105B-	
APPROVED BY:	DATE:				
Jason Nash	09-03-09	SCALE: NTS		U.□.M.:	