


**BES G06E60-PSC15B-EP02**

Inductive Sensors

PNP  
NO  
flush mountable**BALLUFF**

sensors worldwide

CH0170a

**Electrical data:**


Connection	cable
Output resistance (Ra)	open collector
Rated operational voltage (Ue)	24 DC V
Load current capacity (Ie)	150 mA
Rated insulation voltage (Ui)	75 DC
Time delay before availability	20 ms
Electrical type	DC
Utilization category	DC 13
Hysteresis max (H)	15 %
Load capacitance max	0,2 µF
No-load supply current damped	9 mA
No-load supply current undamped	3 mA
Off-state current max (Ir)	10 µA
Ripple max. of Ue	10 %
Switching output	PNP
Switching element function	NO
Operating frequency (f)	3000 Hz
Voltage drop max. static	2,5 V
Supply voltage max. (Ub)	30 V
Supply voltage min. (Ub)	10 V

**Mechanical data:**

Number of wires	3-wire
Rated operating distance (sn)	1,5 mm
Diameter	6,5 mm
Assured operating distance	0...1,2 mm
Cable code designation	PUR
Conductor cross section	3x0,073
Mounting	flush mountable
Ambient temperature max	+70 °C
Ambient temperature min	-25 °C
Degree of pollution	3
Sensing face material	POM
Housing material	corrosion resistance Steel
Repeat accuracy max. (R)	= 5 %

**General data:**

Output indication	yes
Short circuit protected	yes
Brand	SuperShorties
Degree of protection IP	IP67
Insulation class	2
Protected against polarity reversal	yes
Approval	CE,c_ul_us

**wiring****www.balluff.com**Balluff Europe: +49 7158 173 -0  
Balluff USA: 1-800-54 3-83 90  
Balluff Asia: +86 21-50 64 41 31Online Productinformation  
2008-01-24