



Electrical data

Eff. operating voltage Ue DC	24 V
Operating voltage DC (UB)	18 V... 30,2 V
Current sum US (Sensor)	1,2 A
Number of plug-in positions	8

Inputs / Outputs

Number of inputs	8
Inputs	PNP, Type 2
Configurable in-/outputs	No

Bus interface / connection

Transmission protocol	IO-Link 1.0
Data rate min.	38.4 kBaud
Data rate max.	38.4 kBaud

LED indication / Diagnosis

Indicator sensors supply	?
--------------------------	---

Indicator actuators supply	Yes
Indicator switching function	Yes

Mechanical data

Enclosure Type per IEC 60529	IP67 (when connected)
Surface protection	?
Width	50,0 mm
Operating temperature Ta	-5 °C... 55 °C
Storage temperature	-25 °C... 75 °C
Mounting type	3-hole screw mounting
Potting material	UL V-0

Scope of Supply

12x labels
 4x plugs M12
 Short guide

Mounting Instruction

See short guide



Definitions see general catalog

Subject to change without notice.



Input Ports
 PIN 1: +24V, 200mA
 PIN 3: 0V
 PIN 4: Input



IO-Link
 PIN 1: +24V, 1.6A
 PIN 3: 0V
 PIN 4: IO-Link
 PIN 5: Function ground

00000110250160824/20090714