

Electrical data

Eff. operating voltage Ue DC	24 V
Operating voltage DC (UB)	18 V... 30,2 V
Current sum US (Sensor)	1,1 A
Number of plug-in positions	8

Inputs / Outputs

Number of inputs	8
Inputs	PNP, Type 2
Configurable in-/outputs	No

Bus interface / connection

Transmission protocol	IO-Link 1.0
Data rate min.	?
Data rate max.	?

LED indication / Diagnosis

Indicator sensors supply	?
--------------------------	---

Indicator actuators supply	Yes
Indicator switching function	Yes

Mechanical data

Enclosure Type per IEC 60529	IP67 (when connected)
Surface protection	?
Width	30,0 mm
Operating temperature Ta	-5 °C... 55 °C
Storage temperature	-25 °C... 70 °C
Mounting type	2-hole screw mounting
Potting material	UL V-0

Scope of Supply

- 12x labels
- Short guide
- 4x plugs M8


Mounting Instruction

See short guide




Definitions see general catalog

Subject to change without notice.



IO -Link
 PIN 1: +24V
 PIN 3: 0V
 PIN 4: IO-Link
 PIN 5: Function ground



Input Ports
 PIN 1: +24V, 200mA
 PIN 3: 0V
 PIN 4: Input

000000000000164725/00000000