

10-Wire euromfast® Cordsets, Standard Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P and IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
<p>RS ..**</p>	RS 10T-*	AWM PVC Grey 10x24 AWG 105°C 6 mm OD Cable #RF51004- <sup>†</sup> M <sup>†</sup>	<i>flexlife</i> ®	
	RS 10T-*/S90	AWM PUR Grey 10x24 AWG 105°C 6 mm OD Cable #RF51005- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune</i>	
	RS 10T-*/S618	AWM PVC Black 10x24 AWG Foil/Drain 105°C 7 mm OD Cable #RF51076- <sup>†</sup> M <sup>†</sup>	<i>RFI/EMI Shielding</i>	
<p>RSK ..**</p>				
<p>RSV ..**</p>				

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "RS .."; "RSK .." indicates nylon and "RSV .." indicates 316 stainless steel.  
<sup>†</sup> See Section N for *reelfast*® cable information.