

## T&B® Fittings



**T&B Catalog Number:** 2520  
**UPC Number:** 78621002520  
**Description:** 1/2" Liquidtight Strain Relief Cord Connector-Straight; Body Material-Die Cast Zinc; Gland material-Steel; Bushing-Neoprene. Cord range-.125-.250  
**Status:** Active

### General

-Material Die Cast Zinc

### Dimension Information

-Hub Size (inches) 1/2  
 -Dimension A (inches) 1 5/32  
 -Dimension B (inches) 1 11/16  
 -Dimension C (inches) 5/8  
 -Cord Range (inches) .125-.250  
 -Throat Diameter (inches) 9/16

### Specifications

-3dmodel Available on Website

### Packaging

-T&B Inner Pack 25  
 -Package in Units 100  
 -T&B Sold in UOM Each  
 -T&B Weight Per UOM 14.1 lbs. per 100

### Application Support

-Product Overview Available on Website  
 -Specifications Available on Website  
 -Liquidtight Flexible Cord and Cable Connector Applications and Features  
 -Portable Cord Selection Table Available on Website

### Notes

-\*Note Suitable for use in hazardous locations where general purpose eq  
 -\*\*Note Meets Coast Guard CG293  
 -\*\*\*\*Note Temperature rating-105&#176; C

### Certifications

-RoHS Compliance Yes

### Certifications



File Nbr:

E 13938

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 8155 T&B Blvd.  
 Memphis, TN 38125  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 8155 T&B Blvd.  
 Memphis, TN 38125

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com