

## Large Size – Alloys

### LS-1800 and LS-1900 Series are a Step Above Our Plastic Units for Pressure Capabilities

Excellent stability for general use in oils and water.

LS-1800 Series –  
Buna N Float



LS-1800 Series –  
Teflon® Float



LS-1900 Series –  
Buna N Float



Intermediate in size, LS-1800 switches provide long life and dependability to meet a broad range of requirements.

With large float displacement, switch withstands rough service; is suitable for high viscosity liquids.

### Dimensions

LS-1800 Series		LS-1900 Series
Buna N Float	Teflon® Float	Buna N Float
<p>17/32" (13.5 mm) 1/8" NPT 1/2" HEX (12.7 mm) 2-15/16" (74.6 mm) 7/8" (22.2 mm) † 2-13/32" (61.1 mm) 1-3/4" (44.5 mm) 1-1/4" DIA. (31.7 mm)</p>	<p>17/32" (13.5 mm) 1/8" NPT 1/2" HEX (12.7 mm) 2-15/16" (74.6 mm) 7/8" (22.2 mm) † 2-13/32" (61.1 mm) 1-3/4" (44.5 mm) 1-1/4" DIA. (31.75 mm) FLAT WASHER SPRING</p>	<p>21/32" (16.7 mm) 1/4" NPT 5/8" HEX (15.9 mm) 3-3/16" (80.9 mm) 1-3/16" (30.2 mm) † 2-17/32" (64.3 mm) 1-13/16" (46.1 mm) 1-7/8" DIA. (47.6 mm)</p>

†L<sub>1</sub> = Switch actuation level, nominal (based on a liquid specific gravity of 1.0).

### Common Specifications

**Electrical Termination:** No.18 AWG, 24" L., Polymeric Lead Wires.

**Approvals:** All Switches on this page are U.L. Recognized – File No. E45168, and are CSA Listed – File No. 30200.

**Switch Operation:** Selectable, N.O. or N.C., by inverting float on unit stem (except for LS-1800 Series switch with Teflon® float). Units are shipped N.O. unless otherwise specified.

**How To Order – Select Part Number based on specifications required.**

Series Number	Material			Min. Liquid Sp. Gr.	Operating Temperature	Pressure, PSI, Max.	Switch* SPST	Part Number
	Stem and Mounting	Float	Other Wetted					
LS-1800	Brass	Buna N	316 Stainless Steel, Hysol	.75	Water: to 180°F (82°C) Oil: -40°F to +230°F (-40°C to +110°C)	150	20 VA	01801 ⚡
		100 VA**		35651 ⚡				
	316 Stainless Steel	Buna N		.75	20 VA	01807 ⚡		
		Teflon®		.65	100 VA**	35657 ⚡		
LS-1900	Brass	Buna N	316 Stainless Steel, Hysol	.55	Water: to 180°F (82°C) Oil: -40°F to +230°F (-40°C to +110°C)	150	20 VA, N.O.	01811 ⚡
				20 VA			01901 ⚡	
	316 Stainless Steel			.55	100 VA***	35676 ⚡		
				100 VA	35682 ⚡			

\*See "Electrical Data" on Page X-5 for more information.

\*\*\* LS-1900 100VA unit is UL Resistive Rated.

\*\*LS-1800 100 VA switches are not U.L. Recognized.