## RSF40 Compact internal fitting side mounting floatswitch



The RSF40 series is designed as a compact internal fitting device, with a wide range of options, making this ideal for size sensitive applications. Mounting of this series requires access to the inside of the tank.

Typical applications include vending machines, commercial washing machines and evaporator units.

They are manufactured in a variety of materials, with a choice of gasket materials, to suit most commonly used liquids.

The switch action may be reversed by rotating the device through 180°.



- Compact design
- Reliable reed switch contacts
- Available in Nylon, Polypropylene or PPS
- WRAS Approval
- UL Approval (File no E171218)

Technical Specification	RSF48	RSF43	RSF44	RSF46
Material	Polypropylene UL Approved	Nylon	Polypropylene WRAS Approved	Polyphenylene Sulphide (PPS)
Colour	White	Black	Opaque	Grey
Temp. Range°C	-20 / +100	-20 /+75	-20 / +100	-10 / +120*
°F	-4 / +212	-4 / +167	-4 / +212	+14 / +248*
Min. Fluid S.G.	0.85	0.85	0.85	0.85
Must Close Level (S.G.=1)	8mm	7mm	8mm	9mm
Must Open Level (S.G.=1)	20mm	20mm	20mm	24mm

\*Maximum temperature requires ETFE cable to be specified.

Electrical Specification	25W (Y Switch)	100W (H Switch)
Contact Form	N/O (N/C)	N/O (N/C)
Switching Power Max. VA	25VA	100VA
Switching Voltage AC Max.	240V	300V
Switching Voltage DC Max.	120V	300V
Switching Current Max. A	0.6A	1A


All ratings are for resistive load only.

Standard Parts		Leadouts	Gaskets
RSF43H/Y100RF	Nylon	1.0m PVC 16/0.2 UL approved	Nitrile
RSF44H/Y100RF	Polypropylene	1.0m PVC 16/0.2 UL approved	Nitrile
RSF46H/Y100RF	PPS	1.0m PVC 16/0.2 UL approved	Nitrile
RSF48H/Y100RF	Polypropylene (UL)	1.0m PVC 16/0.2 UL approved	Nitrile

 $Custom\ versions\ can\ be\ made\ for\ particular\ applications.\ Please\ contact\ Cynergy 3\ with\ your\ requirements.$ 

## Mechanical Dimensions

All dimensions are in millimeters (inches)



Competitive part number cross-reference available at: www.cynergy3.com

Cynergy3 Components Corporation 11125 Knott Avenue, Suite D, Cypress, CA, 90630. Phone (866) 258-5057 Email: sales@cynergy3.com

USA

EUROPE - UK Cynergy3 Components Ltd. 7 Cobham Road Ferndown Industrial Estate Wimborne, Dorset BH21 7PE Telephone +44 (0) 1202 897969 Fax +44 (0) 1202 891918 Email:sales@cynergy3.com

ISO 9001 CERTIFIED

\*\* Add 10mm to dims, RSF46