




REVISIONS

DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1967		Released	JN	03/26/08	JN	03/26/08	JN	03/26/08



2:1 SHRINK RATIO, MATERIAL: POLYOLEFIN								
Nom. Size (in)	Color	Mfg. Part No.	Spool Size (ft.)	Mfg. Part No.	4" Lengths		6" Lengths	
					Pieces per Pkg.	Mfg. Part No.	Pieces per Pkg.	Mfg. Part No.
3/64 Inch	Red	PP1900	100 FT Spools	PP1912	4 FT Lengths	PP1924	6 Inch Lengths	
1/16 Inch	Red	PP1901	100 FT Spools	PP1913	4 FT Lengths	PP1925	6 Inch Lengths	
3/32 Inch	Red	PP1902	100 FT Spools	PP1914	4 FT Lengths	PP1926	6 Inch Lengths	
1/8 Inch	Red	PP1903	100 FT Spools	PP1915	4 FT Lengths	PP1927	6 Inch Lengths	
3/16 Inch	Red	PP1904	100 FT Spools	PP1916	4 FT Lengths	PP1928	6 Inch Lengths	
1/4 Inch	Red	PP1905	100 FT Spools	PP1917	4 FT Lengths	PP1929	6 Inch Lengths	
3/8 Inch	Red	PP1906	100 FT Spools	PP1918	4 FT Lengths	PP1930	6 Inch Lengths	
1/2 Inch	Red	PP1907	100 FT Spools	PP1919	4 FT Lengths	PP1931	6 Inch Lengths	
3/4 Inch	Red	PP1908	50 FT Spools	PP1920	4 FT Lengths	PP1932	6 Inch Lengths	
1 Inch	Red	PP1909	50 FT Spools	PP1921	4 FT Lengths	PP1933	6 Inch Lengths	
1 1/2 Inch	Red	PP1910	50 FT Spools	PP1922	4 FT Lengths	PP1934	6 Inch Lengths	
2 Inch	Red	PP1911	50 FT Spools	PP1923	4 FT Lengths	PP1935	6 Inch Lengths	
3/64 Inch	Yellow	PP1936	100 FT Spools	PP1948	4 FT Lengths	PP1960	6 Inch Lengths	
1/16 Inch	Yellow	PP1937	100 FT Spools	PP1949	4 FT Lengths	PP1961	6 Inch Lengths	
3/32 Inch	Yellow	PP1938	100 FT Spools	PP1950	4 FT Lengths	PP1962	6 Inch Lengths	
1/8 Inch	Yellow	PP1939	100 FT Spools	PP1951	4 FT Lengths	PP1963	6 Inch Lengths	
3/16 Inch	Yellow	PP1940	100 FT Spools	PP1952	4 FT Lengths	PP1964	6 Inch Lengths	
1/4 Inch	Yellow	PP1941	100 FT Spools	PP1953	4 FT Lengths	PP1965	6 Inch Lengths	
3/8 Inch	Yellow	PP1942	100 FT Spools	PP1954	4 FT Lengths	PP1966	6 Inch Lengths	
1/2 Inch	Yellow	PP1943	100 FT Spools	PP1955	4 FT Lengths	PP1967	6 Inch Lengths	
3/4 Inch	Yellow	PP1944	50 FT Spools	PP1956	4 FT Lengths	PP1968	6 Inch Lengths	
1 Inch	Yellow	PP1945	50 FT Spools	PP1957	4 FT Lengths	PP1969	6 Inch Lengths	
1 1/2 Inch	Yellow	PP1946	50 FT Spools	PP1958	4 FT Lengths	PP1970	6 Inch Lengths	
2 Inch	Yellow	PP1947	50 FT Spools	PP1959	4 FT Lengths	PP1971	6 Inch Lengths	
3/64 Inch	White	PP1972	100 FT Spools	PP1984	4 FT Lengths	PP1996	6 Inch Lengths	
1/16 Inch	White	PP1973	100 FT Spools	PP1985	4 FT Lengths	PP1997	6 Inch Lengths	
3/32 Inch	White	PP1974	100 FT Spools	PP1986	4 FT Lengths	PP1998	6 Inch Lengths	
1/8 Inch	White	PP1975	100 FT Spools	PP1987	4 FT Lengths	PP1999	6 Inch Lengths	
3/16 Inch	White	PP1976	100 FT Spools	PP1988	4 FT Lengths	PP2000	6 Inch Lengths	
1/4 Inch	White	PP1977	100 FT Spools	PP1989	4 FT Lengths	PP2001	6 Inch Lengths	
3/8 Inch	White	PP1978	100 FT Spools	PP1990	4 FT Lengths	PP2002	6 Inch Lengths	
1/2 Inch	White	PP1979	100 FT Spools	PP1991	4 FT Lengths	PP2003	6 Inch Lengths	
3/4 Inch	White	PP1980	50 FT Spools	PP1992	4 FT Lengths	PP2004	6 Inch Lengths	
1 Inch	White	PP1981	50 FT Spools	PP1993	4 FT Lengths	PP2005	6 Inch Lengths	
1 1/2 Inch	White	PP1982	50 FT Spools	PP1994	4 FT Lengths	PP2006	6 Inch Lengths	
2 Inch	White	PP1983	50 FT Spools	PP1995	4 FT Lengths	PP2007	6 Inch Lengths	
3/64 Inch	Blue	PP2008	100 FT Spools	PP2020	4 FT Lengths	PP2032	6 Inch Lengths	
1/16 Inch	Blue	PP2009	100 FT Spools	PP2021	4 FT Lengths	PP2033	6 Inch Lengths	
3/32 Inch	Blue	PP2010	100 FT Spools	PP2022	4 FT Lengths	PP2034	6 Inch Lengths	
1/8 Inch	Blue	PP2011	100 FT Spools	PP2023	4 FT Lengths	PP2035	6 Inch Lengths	
3/16 Inch	Blue	PP2012	100 FT Spools	PP2024	4 FT Lengths	PP2036	6 Inch Lengths	
1/4 Inch	Blue	PP2013	100 FT Spools	PP2025	4 FT Lengths	PP2037	6 Inch Lengths	
3/8 Inch	Blue	PP2014	100 FT Spools	PP2026	4 FT Lengths	PP2038	6 Inch Lengths	
1/2 Inch	Blue	PP2015	100 FT Spools	PP2027	4 FT Lengths	PP2039	6 Inch Lengths	
3/4 Inch	Blue	PP2016	50 FT Spools	PP2028	4 FT Lengths	PP2040	6 Inch Lengths	
1 Inch	Blue	PP2017	50 FT Spools	PP2029	4 FT Lengths	PP2041	6 Inch Lengths	
1 1/2 Inch	Blue	PP2018	50 FT Spools	PP2030	4 FT Lengths	PP2042	6 Inch Lengths	
2 Inch	Blue	PP2019	50 FT Spools	PP2031	4 FT Lengths	PP2043	6 Inch Lengths	
3/64 Inch	Brown	PP2044	100 FT Spools	PP2056	4 FT Lengths	PP2068	6 Inch Lengths	
1/16 Inch	Brown	PP2045	100 FT Spools	PP2057	4 FT Lengths	PP2069	6 Inch Lengths	
3/32 Inch	Brown	PP2046	100 FT Spools	PP2058	4 FT Lengths	PP2070	6 Inch Lengths	
1/8 Inch	Brown	PP2047	100 FT Spools	PP2059	4 FT Lengths	PP2071	6 Inch Lengths	
3/16 Inch	Brown	PP2048	100 FT Spools	PP2060	4 FT Lengths	PP2072	6 Inch Lengths	
1/4 Inch	Brown	PP2049	100 FT Spools	PP2061	4 FT Lengths	PP2073	6 Inch Lengths	
3/8 Inch	Brown	PP2050	100 FT Spools	PP2062	4 FT Lengths	PP2074	6 Inch Lengths	
1/2 Inch	Brown	PP2051	100 FT Spools	PP2063	4 FT Lengths	PP2075	6 Inch Lengths	
3/4 Inch	Brown	PP2052	50 FT Spools	PP2064	4 FT Lengths	PP2076	6 Inch Lengths	
1 Inch	Brown	PP2053	50 FT Spools	PP2065	4 FT Lengths	PP2077	6 Inch Lengths	
1 1/2 Inch	Brown	PP2054	50 FT Spools	PP2066	4 FT Lengths	PP2078	6 Inch Lengths	
2 Inch	Brown	PP2055	50 FT Spools	PP2067	4 FT Lengths	PP2079	6 Inch Lengths	
3/64 Inch	Gray	PP2080	100 FT Spools	PP2092	4 FT Lengths	PP2104	6 Inch Lengths	
1/16 Inch	Gray	PP2081	100 FT Spools	PP2093	4 FT Lengths	PP2105	6 Inch Lengths	
3/32 Inch	Gray	PP2082	100 FT Spools	PP2094	4 FT Lengths	PP2106	6 Inch Lengths	
1/8 Inch	Gray	PP2083	100 FT Spools	PP2095	4 FT Lengths	PP2107	6 Inch Lengths	
3/16 Inch	Gray	PP2084	100 FT Spools	PP2096	4 FT Lengths	PP2108	6 Inch Lengths	
1/4 Inch	Gray	PP2085	100 FT Spools	PP2097	4 FT Lengths	PP2109	6 Inch Lengths	
3/8 Inch	Gray	PP2086	100 FT Spools	PP2098	4 FT Lengths	PP2110	6 Inch Lengths	
1/2 Inch	Gray	PP2087	100 FT Spools	PP2099	4 FT Lengths	PP2111	6 Inch Lengths	
3/4 Inch	Gray	PP2088	50 FT Spools	PP2100	4 FT Lengths	PP2112	6 Inch Lengths	
1 Inch	Gray	PP2089	50 FT Spools	PP2101	4 FT Lengths	PP2113	6 Inch Lengths	

Note:

- Operating temperature -55°C to +125°C
- Minimum shrink temperature 70°C
- Shrink Ratio 2:1
- Approvals: UL224, 125°C 600V VW-1
- CSA22.2 No.198.1 125°C 600V, OFT

Technical Data

Property	Test Method	Typical Data
Tensile Strength	ASTM D 2671	14MPa
Ultimate Elongation (%)	ASTM D 2671	450
Longitudinal Shrinkage (%)	UL 224	+/- 5
Heat Aging Tensile Strength Ultimate Elongation (%)	158 ? , 168hr	11MPa 300
Flammability	UL224 VW-1	Pass
Heat shock (250 ? , 4hrs)	ASTM D 2671	No cracking
Cold bend tests (-55 ? , 4hrs)	ASTM D 2671	No cracking
Dielectric Strength (kv/mm)	ASTM D 150	20
Volume Resistivity (ohm-cm)	ASTM D 876	1x10 ¹⁴
Copper Stability	UL224	Pass

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jason Nash	03/26/08	Heat Shrink Tubing; 2:1 Ratio			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	Jason Nash	03/26/08	A	TA-849	TA-849	A
	APPROVED BY:	DATE:	SCALE: NTS		U.O.M.: INCHES [mm]	SHEET: 1 OF 1
	Jason Nash	03/26/08				

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.