LABILITY WHATSOEVER IN CONNECTION THEREWITH.	FOR THE INTENDED USE AND ASSUME ALL RISK AND	CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE	HEREIN ARE BASED UPON INFORMATION AND/OR LESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE	ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED	DISCI AIMER.	<ol> <li>Temperature Rating: -40°F to 200°F.</li> <li>All flame retardants must pass horizontal flame test.</li> <li>All flame retardants must pass horizontal flame test.</li> <li>UL-94 V2 rated at 1.5 mm.</li> <li>UL-94 V2 rated at 101.2 mm / min (1.0 mm thick) Self-extinguishing.</li> <li>FMVSS rated at 101.2 mm / min (1.0 mm thick) Self-extinguishing.</li> <li>All "UL" and FMVSS 302 flame ratings are for the resin used to manufacture our product, not for our end product. The ratings are created by testing standard "UL" and "FMVSS" plaque specimens, not tubing samples</li> <li>All "UL" and FMVSS 302 flame ratings are for the resin used to manufacture our product, not for our end product. The ratings are created by testing standard "UL" and "FMVSS" plaque specimens, not tubing samples</li> </ol>	Notes :					Dimensions : Inches (mm)								-				
PORPLASES LINET.		DIME	SPECIFIED,		TOLERANCES: D	st. elf-extinguishing. resin used to manufacture our product, not fo															SPC-F005.DWG	ECHNOLOGY.	WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED	LL RIGHTS RESERVED. NO PORTION OF THIS
	APPROVED BY:	MRD 2	CHECKED BY:	AMU	DRAWN BY:	r our end product. The rating:								-	 	 	⊳ -	 		-			REPRODUCED DCP #	S PUBLICATION,
14-11-10	DATE:	25-10-10	DATE:	25-10-10	DATE:	s are created by	1434	1432 1433	1431	1429 1430	Manufacturer Part Number		-		 	 	B -	 	 	-			REV	
SCALE: NTS		$\approx$	SIZE DWG. NO.	Gray Flame	67	testing standard "UL	0.991" 1.274"	0.739" 0.966"	+	0.363" 0.389"	A±0.15 (inches)	-											DESCRIPTION	REVISIONS
U.O.M.:		1430	0.	Retardent	) - -	_" and "FMVSS" plaque speci	1" Gray Polyethylene Slit Loom - 50' spool	3/4" Gray Polyethylene Slit Loom - 50' spool	1/2" Gray Polyethylene-FR Slit Loom - 100' spool	1/4" Gray Polyethylene-FR Slit Loom - 100 spool 3/8" Gray Polyethylene-FR Slit Loom - 100 spool		-								-				
INCHES [mm]				Polyethylene	-	mens, not tubing	_oom - 50' spool	t Loom - 50' spoc	R Slit Loom - 100	R Slit Loom - 100										-		AMU 25-10-1	DRAWN DATE	DOC. NO. SPC-F005
			ELECTRONIC	ne Slit		samples.		spool	spool	spool	-											0 MRD 25	CHECKD	*
SHEET:	1 -	·A−122	NIC FILE	Loom															Compl	5		-10-10 X>	DATE APF	Effective: 7/8/02 *
→ Pr →	oad	⊳ ed i	REV	guidn I		s.com electronic comp	onem	s dist	ribut	or									RoHS Compliant	-		<x 14-11-10<="" td=""><td>APPRVD DATE</td><td>DCP No: 1398</td></x>	APPRVD DATE	DCP No: 1398