
of all type of professional audio equipment A range of phono leads designed to enhance sound quality of interconnection

conductor, polyethelene insulation and double lapped copper shield. Low loss Gotham GAC-1 single core audio cable with stranded copper

with gold plated contacts and black finished cap. Fully shielded professional phono plugs manufactured from machined brass

Available in pairs, colour coded red and black. Hand soldered and individually tested for reliability.

Dimensions



CONDUCTOR INSULATION INNER SLEEVE PVC, Ø5.3mm Conductor PVC. Lapped 0.1mm stranded copper. Lapped 0.1mm stranded copper. 48x0.07mm stranded copper Polyethelene 1.25mm


SHIELD 2

SHIELD 1 JACKET CABLE

Brass, 0.5 microns gold plated. Brass, 0.5 microns gold plated. Brass, black chrome plated.

CAP SHIELD CONTACT

CONNECTOR



ONE PAIR RED AND BLACK (3,0 m)	061-0030
ONE PAIR RED AND BLACK (2,0 m)	061-0020
ONE PAIR RED AND BLACK (1,0 m)	061-0010
ONE PAIR RED AND BLACK (0,5 m)	061-0005
Description	Deltron Part No.

CONVERTED FROM PS0365 ISS3 (02.12.93) IN JAN 2003

Dahk	

Aprvd Dat	SERIES	FOR 061	
CUSTOME	SPECIFICATION	GENERAL	

TITLE HIGH DEFINITION PHONO

LEADS

© Deltron Emcon Limited E—Mail components@deltron—emcon.com, Website www.deltron—emcon.com. Phone	FOR 061 SERIES	
Website www.deltron-emco	SERIES	GENERAL SPECIFICATION
n.com. Phone +44 1724 273200 Fax +44 1724 270230	Aprvd Date 10/02/03 Aprvd By MC	CUSTOMER
+44 1724 270230	Drwn by BFS	FILTER REF

Scale: NTS Sheet 1/

DELTRON

#

ALL DIMENSIONS IN MM ANGLES IN DECIMAL DEGREES