



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
B	ECN# 1965: CHANGING BRAIDED SHIELD TO SPIRAL STYLE	01/31/05	M.LAHEY
C	ECN# 2286 ADDED ARROW TO TYPE A PLUG	01/04/06	MCCORMICK
D	ECN# 2305 REVISED EXPANDED LENGTH FROM 10.5 FEET	02/01/06	MCCORMICK
E	ECN# 2419 ADDED .463" MIN DIMENSION	05/18/06	MCCORMICK



WIRING DIAGRAM



- NOTES:**
1. THESE CABLE ASSEMBLIES ARE CONSTRUCTED TO MEET THE REQUIREMENTS OF THE UNIVERSAL SERIES BUS SPECIFICATION USB 2.0.
 2. CONNECTOR CONTACTS HAVE 30 MICROINCHES GOLD PLATING OVER NICKEL PLATING.
 3. THE CABLE SHIELD DRAIN WIRE IS CONNECTED TO THE METAL SHELL OF EACH PLUG.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES
 TOLERANCES ARE:
 .X ± .1
 .XX ± .05
 .XXX ± .005
 CABLE LENGTH TOLERANCE
 <300' ± 5% >300' ± 2%

APPROVALS	DATE
DRAWN BY C.MCCORMICK	10/01/2004
CHECKED BY D.PARHAM	10/01/2004
APPROVED BY R.CARRICK	10/01/2004

L-com 45 BEECHWOOD DRIVE
 NORTH ANDOVER, MA 01845

CONNECTIVITY PRODUCTS

PRODUCT DESCRIPTION
TYPE "A" LATCHING PLUG TO TYPE "B" PLUG

DRAWING TITLE
OUTLINE DRAWING

SIZE A	FSCM NO. 43321	DWG. NO. COILUAB-OD1	REV. E
SCALE: NONE	CAD FILE: COILUAB-OD1.SLDDRW	SHEET 1 OF 1	

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY