	. RIGHTS RESERVED. NO PORTION OF THIS PUBLICATIOI	N	REVISIONS				DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398					
	ETHER IN WHOLE OR IN PART CAN BE REPRODUCED HOUT THE EXPRESS WRITTEN CONSENT OF SPC	DCP #	REV	DESCRIPTION			DATE	СНЕСКО	DATE	APPRVD	DATE	
	CHNOLOGY.	1906	A		RELEASED	EO	04/17/06	TL	05/25/06	но	05/25/06	
TECHNOLOGY	C-F005.DWG											
		Typical Co	onnector Di	IEEE-1284			CO C			· BRAID · DW	P FAL/MY	
C) PVC - 45P, Platin 2. Cable: [28AWG (7/0.127)*18]	PE nd 360° solder to connector um gray P+FO-PP 163)+85%BD(24/8/0.12)]TIN .63±0.05MM = \$8.0±0.20mm E plating	I BL 1 BL 2 BR 3 R 4 ORA 5 YEL 6 GR 7 BI 8 PUI 9 WH 10 GF 11 PINH	OWN ED ANGE CONTROLOGY EEN CONTROLOG	LE MALE 1 13 2 14 3 16 4 15 5 17 6 18 7 19 8 19 9 20	WIRE COLORDB25 MALEYELLOW/RED13LIGHT-GREEN14LIGHT-BLUE16WHITE/RED15PINK17BLACK/WHITE18BROWN/BLACK19ORANGE/BLACK19ORANGE/BLACK20YELLOW/BLACK21BLUE/BLACK21	MALE 22 24 23 24 23 24 25	WIRE COL PURPLE/E WHITE/BL ORAY/BL PINK/WH DRANGE/V YELLOW/W HHT-GREEI GHT-BLUE RED/WH PINK/BL RED & G	BLACK ACK ACK HITE WHITE WHITE N/BLACK ITE ACK	25 23 25			
DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINE HEREIN ARE BASED UPON INFORMATION AND/OR TESTS BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODU FOR THE INTENDED USE AND ASSUME ALL RISK AND LIBUILTY WHATSOEVER IN CONNECTION THEREWITH.	WE SPECIFIED, CHECKED B DIMENSIONS ARE	SH IY: E	DATE: 04/17/0 DATE: 05/25/0 DATE:	6 IEE	G TITLE: E 1284 Printer DWG. NO. SPC1 NTS			ELECT 83	RONIC FI	LE	REV A	

HISHAM ODISH

05/25/06