



- 1.CABLE:10 PCS NO UL.28AWG(7/0.127),TINNED AND STRANDED COPPER WIRE
JACKET:PVC,COMPLIANCE ROHS
- 2.1PCS CONNECTOR#D-SUB 9 WAYS FEMALE SOLDER TYPE CONNECTOR
INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE
CONTACT:COPPER ALLOY,GOLD FLASH OVER NICKEL PLATED
SHELL:NICKEL PLATED.
CONNECTOR COMPLIANCE ROHS
- 3.1PCS CONNECTOR#D-SUB 25 WAYS MALE SOLDER TYPE CONNECTOR
INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE
CONTACT:COPPER ALLOY,GOLD FLASH OVER NICKEL PLATED
SHELL :NICKEL PLATED.
CONNECTOR COMPLIANCE ROHS
- 4 2PCS 5*6 NUTS, COMPLIANCE ROHS
- 5 HOOD:PVC MOLDED TYPE ON INNER MOLD AND INJECTION
OUTER MOLD WITH THUMB SCREW#4-22 UNC
COLOR:BEIGE,COMPLIANCE ROHS
- 6 Fulfill ROHS Guideline
- 7 ELECTRONIC TEST
100% OPEN SHORT+MISS WIRE TEST

DRAWING

DB9PIN JACK(J1)	WIRE	DB25PIN MALE(P1)
1	—————	8
2	—————	3
3	—————	2
4	—————	20
5	—————	7
6	—————	6
7	—————	4
8	—————	5
9	—————	22
SHELL	—————	SHELL



PART NO 1052	SHEET NO 1	THIRD ANGLE PROJECTION
TITLE: ADAPTER DB9 PIN FEMALE TO DB25 PIN MALE BEIGE COLOR		SCALE N.T.S DRAWN BY & DATE
DWN NO		SIZE A4 UNIT CHECKED BY & DATE
		<input checked="" type="checkbox"/> MM <input type="checkbox"/> INCH APPROVED BY & DATE