



79516	
P/N	LENGTH
79516-1061	1000 +/-50MM
79516-1063	3000 +/-100MM
79516-1065	5000 +/-150MM

NOTES:
 1. PIN CONNECTION IN 1 TO 1.
 2. LABEL CABLE WITH FOLLOWING INFORMATION:
 P/N (SEE TABLE)
 REV. (SEE REVISION TABLE)
 M/D WW/YY
 ASSEMBLED IN MEXICO

ITEM	P/N	DESCRIPTION	QTY
6	0799426019	PLASTIC LABEL EPC#R-TW10F	1 PC
5	0799300115	TAPON MICROFIT 6 CKT STD	2 PC
4	0899920428	PVC 15% MF BLACK UL94V-2	A/R
3	0430300004	MicroFit 3.0 F Crp Term Chn Tin 26-30	12 PC
2	0430250600	MicroFit 3.0 DR Rcpt PnlMnt 2Ckt	2 PC
1	799232212	CABLE 6 COND, 26AWG, JACKETED	A/R

RELEASED EC NO: MEX2005-0077 DRWN: AOROZCO 2004/12/16 CHKD: GVILLAGRA2004/12/16 APPR: GVILLAGRA2004/12/17	DESCRIPTION A	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY																
		$\nabla - 0$ $\sphericalangle - 0$	<table border="1"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.3</td> <td>± ---</td> </tr> <tr> <td>1 PLACE</td> <td>± ---</td> <td>± ---</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± ---	2 PLACES	± 0.3	± ---	1 PLACE	± ---	± ---	DIMENSION STYLE MM ONLY	TITLE MICRO-FIT OVERMOLDED ASSEMBLY 6 CKT 1, 3 & 5 MTS.			
			mm	INCH																			
		4 PLACES	± ---	± ---																			
3 PLACES	± ---	± ---																					
2 PLACES	± 0.3	± ---																					
1 PLACE	± ---	± ---																					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		DRAWN BY AOROZCO DATE 10/10/2003 CHECKED BY AOROZCO DATE 10/10/2003 APPROVED BY ACUEVAS DATE 10/10/2003	MOLEX INCORPORATED MATERIAL NO. VARIOS DOCUMENT NO. SD-79516-003		SHEET NO. 1 OF 1																		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																							

tb_frame_A_P_ME_T
 Rev. C 2002/05/05