


NOTE:
 PHYSICAL
 1. INNER MOLD WITH PE RESIN 887800008;
 OUTER MOLD WITH BLACK PVC RESIN 887800019.
 2. INNER MOLD WITH PE RESIN 887800008;
 OUTER MOLD WITH BLACK PVC RESIN 887800042.
 ELECTRICAL PERFORMANCE:
 3. DIELECTRONIC STRENGTH:500V DC
 4. INSULATION RESISTANCE:100M OHMS Min.
 5. CONDUCTIVE RESISTOR: 2 OHMS Max.



887625410	1000mm	40 INCH
887625400	500mm	20 INCH
MOLEX P/N	LENGTH	LENGTH

C	S-ATA STRAIGHT CONN. 675380001		I
B	2PX26AWG S-ATA CABLE RED 887808052	N/A	I
A	S-ATA R/A CONN. 887899745		I
ITEM	DESCRIPTION	L	QTY.

EC NO. DRWN: Louis 04/02/17 CHK: APPR:	DESCRIPTION REV	QUALITY SYMBOLS MAJOR ▼ = 0 CRITICAL ▽ = 0	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE N.T.S	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	THIRD ANGLE PROJECTION <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH <input type="checkbox"/> mm ONLY	SHT	REV													
			<table border="1"> <tr> <td></td> <td>mm</td> <td>INCH</td> </tr> <tr> <td>4 PLACES</td> <td>±0.1</td> <td>±.</td> </tr> <tr> <td>3 PLACES</td> <td>±0.1</td> <td>±.</td> </tr> <tr> <td>2 PLACES</td> <td>±0.1</td> <td>±.</td> </tr> <tr> <td>1 PLACE</td> <td>±0.1</td> <td>±.</td> </tr> </table>		mm	INCH	4 PLACES	±0.1	±.	3 PLACES	±0.1	±.	2 PLACES	±0.1	±.	1 PLACE	±0.1	±.	DRAWN BY & DATE Louis Chen 03/11/24	TITLE: S-ATA STRAIGHT TO RIGHT ANGEL SIGNAL RED CABLE, 0.5M, 1M	
	mm	INCH																			
4 PLACES	±0.1	±.																			
3 PLACES	±0.1	±.																			
2 PLACES	±0.1	±.																			
1 PLACE	±0.1	±.																			
A			ANGULAR: ± 0	CHECKED BY & DATE Luky Xu 03/11/24	APPROVED BY & DATE Stepher Guo 03/11/24	MOLEX INCORPORATED															
				CAD FILENAME J6254-XX .DGN	MATERIAL NO. 8876254XX	DRAWING NO. SD-88755-009	SHEET NO. 1 OF 1	SIZE A4													
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.																					

WBORD_A.BOR REV A
 97/05/14 LEVEL 3

