



DATE	REV	DESCRIPTION	BY	CHKD

Marking: CAT.6 26AWGX4PR SSTP IEC 60332.1 PATCH
 CABLE - CONFORM TO ISO/IEC 11801 & EN 50288 &
 TIA/EIA-568-B.2-1 3P/ETL VERIFIED
 Insulating
 (Foam-Skin)



orange 1	green 2
white	white
blue 3	brown 4
white	white

Conductor	Class Copper 26AWG 19, 1.27x0.80mm
Insulation	Thickness 30M at any point 0.2mm MAX. A VULC. 5mm Diameter: 1.27x0.81mm
Jacketing PVC	Thickness 30M at any point 0.40mm MAX. A VULC. 5mm Diameter: 1.41x0.2mm



WIRE	CAT.6 P/MP SER 26AWG4P
PLUG	YS-02 8P/SC 50u
LENGTH	1M
COLOR	GY825

PA/R	PINOUT		
	P1 (T568B)	WIRE	P2 (T568B)
1	1	WHT/ORG	1
	2	ORG	2
2	3	WHT/GRN	3
	6	GRN	6
3	4	BLU	4
	5	WHT/BLU	5
4	7	WHT/BRN	7
	8	BRN	8

RoHS Compliant

Unless specified on the drawing, tolerances are per the follows:
 ± 1
 .X ± 0.2
 .XX ± 0.05



DRAW. NO	YS-02	ITEM	2992-1		
DEPARTMENT		DRAW	ZhaoyangWu	DATE	2007/06/07
SCALE		CHECKER		APPROVAL	
UNIT	MM	SHEET	1	OF	1